# Clouds and the Earth's Radiant Energy System (CERES)

# Data Management System

# Operator's Manual

**CERES ERBE-like Inversion to Instantaneous TOA Fluxes (Subsystem 2.0)**

**CER2.1P1**
**CER2.2P1**
**CER2.3P1**
**CER2.3P2**
**CER2.4P1**

**Release 4**
**Version 1**

*Edward Kizer*
*Dale Walikainen*
*Beth Flug*

Science Applications International Corporation (SAIC)
One Enterprise Parkway, Suite 300
Hampton, VA 23666

NASA Langley Research Center
Radiation and Aerosols Branch
Atmospheric Sciences Competency
21 Langley Boulevard
Hampton, VA 23681-2199

SW Delivered to CM: April 2003
Document Date: April 2003

# Document Revision Record

The Document Revision Record contains information pertaining to approved document changes. The table lists the date the Software Configuration Change Request (SCCR) was approved, the Release and Version Number, the SCCR number, a short description of the revision, and the revised sections. The document authors are listed on the cover. The Head of the CERES Data Management Team approves or disapproves the requested changes based on recommendations of the Configuration Control Board.

Document Revision Record (1 of 2)

| SCCR Approval Date | Release/ Version Number | SCCR Number | Description of Revision | Section(s) Affected |
|---|---|---|---|---|
| 06/21/01 | R3V5 | 271 | • Added new Instrument Configuration code "CC1_2".<br>• Updated command line options for CER2.2P1, CER2.3P1, and CER2.3P2 PCF generators.<br>• Added exit codes, screen messages and Logfile error messages.<br>• Introduced ERBE S-8 data as alternate input dataset.<br>• Updated format to comply with standards. | 2.2.2, 3.2.2, & 4.2.2<br>2.2.1, 2.2.5, 2.4.1, 3.2.1., 3.4.1, 4.2.1, & 4.4.1<br>2.5.1, 2.5.2, 3.5.1, 3.5.2, 4.5.1, & 4.5.2<br>2.3.2, 3.3.2, & 4.3.2<br>All |
| 04/26/02 | R3V6 | 341 | • Added new PGE 2.4P1.<br>• Added new runtime parameter command line option for "spcor".<br>• Added input data set sections for CER2.4P1 target PGEs.<br>• Added error messages for new PGE 2.4P1.<br>• Added example of Ascii Input file for new PGE 2.4P1.<br>• Adjusted capitalization of runtime parameter YYYYMMDD to yyyymmdd.<br>• Added PCF, PCFin, and Toolkit Log files to the Expected output file listings.<br>• Removed /QA from Expected output file listings destination column.<br>• Updated format to comply with standards. | Introduction, 5.0<br>3.1.3, 3.2.2, 4.1.3, 4.2.2<br>2.2.1, 2.4.1, 3.2.1, 3.4.1, 4.2.1, 4.4.1<br>2.3.4, 3.3.4, 4.3.4<br>Appendix B<br>Appendix C<br>1.6, 2.6<br>1.6, 2.6, 3.6, 4.6, 5.6<br>1.6, 2.6, 3.6, 4.6, 5.6<br>All |

Document Revision Record (2 of 2)

| SCCR Approval Date | Release/ Version Number | SCCR Number | Description of Revision | Section(s) Affected |
|---|---|---|---|---|
| 04/17/03 | R4V1 | 432 | • Added new Exit codes for PGE 2.4P1.<br>• Added new Screen Messages for execution of CER2.4P1.<br>• Added new output files produced in PGE 2.4P1.<br>• Added references to new PGE CER3.2P2.<br>• Updated format to comply with standards. | Table 5-3<br>Table 5-4<br>Table 5-5<br>Table 2-2.<br>All |

# Preface

The Clouds and the Earth's Radiant Energy System (CERES) Data Management System supports the data processing needs of the CERES Science Team research to increase understanding of the Earth's climate and radiant environment. The CERES Data Management Team works with the CERES Science Team to develop the software necessary to support the science algorithms. This software, being developed to operate at the Langley Atmospheric Sciences Data Center (ASDC), produces an extensive set of science data products.

The Data Management System consists of 12 subsystems; each subsystem represents one or more stand-alone executable programs. Each subsystem executes when all of its required input data sets are available and produces one or more archival science products.

This Operator's Manual is written for the data processing operations staff at the Langley ASDC by the Data Management Team responsible for this Subsystem. Each volume describes all Product Generation Executables for a particular subsystem and contains the Runtime Parameters, Production Request Parameters, the required inputs, the steps used to execute, and the expected outputs for each executable included within this Subsystem. In addition, all subsystem error messages and subsequent actions required by the ASDC operations staff are included.

Acknowledgment is given to Yvonne M. Seaman and Waldena Banks of Science Applications International Corporation (SAIC) for their support in the preparation of this document and to Maria Vallas Mitchum, NASA Langley Research Center, and Sandra K. Nolan, SAIC, for structuring the manual guidelines and organization.

# TABLE OF CONTENTS

Section Page

Preface . . . . . iv
Introduction . . . . . 1
Document Overview . . . . . 1
Subsystem Overview . . . . . 2
ERBE-like (Subsystems 2.0 and 3.0) Processing (FAPS+RAPS) Overview . . . . . 3
1.0 PGEName: CER2.1P1 . . . . . 5
1.1 PGE Details . . . . . 5
1.1.1 Responsible Persons . . . . . 5
1.1.2 E-mail Distribution List . . . . . 5
1.1.3 Parent PGE(s) . . . . . 5
1.1.4 Target PGE(s) . . . . . 6
1.2 Operating Environment . . . . . 6
1.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.) . . . . . 6
1.2.2 Environment Script Requirements . . . . . 6
1.2.3 Execution Frequency (daily,hourly,..) . . . . . 7
1.2.4 Memory/Disk Space/Time Requirements . . . . . 7
1.2.5 Restrictions Imposed in Processing Order . . . . . 7
1.3 Processor Dependencies (Previous PGEs, Ingest Data,..) . . . . . 7
1.3.1 Input Dataset Name (#1): NISE_SSMIF13 . . . . . 7
1.4 Operating Procedures (Procedure for each part of the processor's elements) . . . . . 8
1.4.1 How to Generate the ASCII File and PCF . . . . . 8
1.4.2 How to Execute the Main-Processor . . . . . 8
1.4.3 Special Case Considerations . . . . . 8
1.4.4 Special Reprocessing Instructions . . . . . 9
1.5 Execution Evaluation . . . . . 9
1.5.1 Exit Codes . . . . . 9
1.5.2 Screen Messages (Use Table format for large number of messages) . . . . . 10
1.5.3 Log and Status Files Results (Include ALL Log Files) . . . . . 10
1.5.3.1 Report Log File: CER2.1P1_LogReport_$SS2_1_$PS2_1_$CC2_1.yyyymm . . . . . 10
1.5.3.2 Status Log File: CER2.1P1_LogStatus_$SS2_1_$PS2_1_$CC2_1.yyyymm . . . . . 10
1.5.3.3 User Log File: CER2.1P1_LogUser_$SS2_1_$PS2_1_$CC2_1.yyyymm . . . . . 11

# TABLE OF CONTENTS

Section Page


1.5.4 Solutions to Possible Problems . . . . . 11
1.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing) . . . . . 11
1.6 Expected Output Dataset(s) . . . . . 11
1.7 Expected Temporary Files/Directories . . . . . 12
2.0 PGEName: CER2.2P1 . . . . . 13
2.1 PGE Details . . . . . 13
2.1.1 Responsible Persons . . . . . 13
2.1.2 E-mail Distribution List . . . . . 13
2.1.3 Parent PGE(s) . . . . . 13
2.1.4 Target PGE(s) . . . . . 13
2.2 Operating Environment . . . . . 14
2.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.) . . . . . 14
2.2.2 Environment Script Requirements . . . . . 14
2.2.3 Execution Frequency (daily,hourly,..) . . . . . 15
2.2.4 Memory/Disk Space/Time Requirements . . . . . 15
2.2.5 Restrictions Imposed in Processing Order . . . . . 15
2.3 Processor Dependencies (Previous PGEs, Ingest Data,..) . . . . . 16
2.3.1 Input Dataset Name (#1): preES-8 . . . . . 16
2.3.2 Alternate Dataset Name (#1): S-8 . . . . . 17
2.3.3 Input Dataset Name (#2): SNOW . . . . . 17
2.3.4 Input Dataset Name (#3): Spectral Response and Correction Coefficients . . . . . 18
2.4 Operating Procedures (Procedure for each part of the processor's elements) . . . . . 18
2.4.1 How to Generate the ASCII File and PCF . . . . . 19
2.4.2 How to Execute the Main-Processor . . . . . 19
2.4.3 Special Case Considerations . . . . . 19
2.4.4 Special Reprocessing Instructions . . . . . 20
2.5 Execution Evaluation . . . . . 20
2.5.1 Exit Codes . . . . . 20
2.5.2 Screen Messages (Use Table format for large number of messages) . . . 21
2.5.3 Log and Status Files Results (Include ALL Log Files) . . . . . 22
2.5.3.1 Report Log File: CER2.2P1_LogReport_$SS2_$PS2_$CC2.yyyymmdd . . . . . 22

# TABLE OF CONTENTS

Section Page


2.5.3.2 Status Log File: CER2.2P1_LogStatus_$SS2_ $PS2_$CC2.yyyymmdd . . . . . 22
2.5.3.3 User Log File: CER2.2P1_LogUser_$SS2_ $PS2_$CC2.yyyymmdd . . . . . 22
2.5.4 Solutions to Possible Problems . . . . . 23
2.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing) . . . . . 23
2.6 Expected Output Dataset(s) . . . . . 23
2.7 Expected Temporary Files/Directories. . . . . 24
3.0 PGEName: CER2.3P1 . . . . . 25
3.1 PGE Details . . . . . 25
3.1.1 Responsible Persons . . . . . 25
3.1.2 E-mail Distribution List . . . . . 25
3.1.3 Parent PGE(s) . . . . . 25
3.1.4 Target PGE(s) . . . . . 25
3.2 Operating Environment . . . . . 26
3.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.) . . . . . 26
3.2.2 Environment Script Requirements . . . . . 26
3.2.3 Execution Frequency (daily,hourly,..) . . . . . 27
3.2.4 Memory/Disk Space/Time Requirements . . . . . 27
3.2.5 Restrictions Imposed in Processing Order . . . . . 27
3.3 Processor Dependencies (Previous PGEs, Ingest Data,..) . . . . . 27
3.3.1 Input Dataset Name (#1): preES-8 . . . . . 27
3.3.2 Alternate Dataset Name (#1): S-8 . . . . . 28
3.3.3 Input Dataset Name (#2): SNOW . . . . . 28
3.3.4 Input Dataset Name (#3): Spectral Response and Correction Coefficients . . . . . 29
3.4 Operating Procedures (Procedure for each part of the processor's elements) . . . . . 29
3.4.1 How to Generate the ASCII File and PCF . . . . . 29
3.4.2 How to Execute the Main-Processor . . . . . 30
3.4.3 Special Case Considerations . . . . . 30
3.4.4 Special Reprocessing Instructions . . . . . 30
3.5 Execution Evaluation . . . . . 31
3.5.1 Exit Codes . . . . . 31

# TABLE OF CONTENTS

Section Page


3.5.2 Screen Messages (Use Table format for large number of messages.) . . . . . 31
3.5.3 Log and Status Files Results (Include ALL Log Files) . . . . . 32
3.5.3.1 Report Log File: CER2.3P1_LogReport_$SS2_$PS2_$CC2.yyyymmdd . . . . . 32
3.5.3.2 Status Log File: CER2.3P1_LogStatus_$SS2_$PS2_$CC2.yyyymmdd . . . . . 32
3.5.3.3 User Log File: CER2.3P1_LogUser_$SS2_$PS2_$CC2.yyyymmdd . . . . . 32
3.5.4 Solutions to Possible Problems . . . . . 33
3.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing) . . . . . 33
3.6 Expected Output Dataset(s) . . . . . 33
3.7 Expected Temporary Files/Directories. . . . . 34
4.0 PGEName: CER2.3P2 . . . . . 35
4.1 PGE Details . . . . . 35
4.1.1 Responsible Persons . . . . . 35
4.1.2 E-mail Distribution List . . . . . 35
4.1.3 Parent PGE(s) . . . . . 35
4.1.4 Target PGE(s) . . . . . 35
4.2 Operating Environment . . . . . 36
4.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.) . . . . . 36
4.2.2 Environment Script Requirements . . . . . 36
4.2.3 Execution Frequency (daily,hourly,..) . . . . . 37
4.2.4 Memory/Disk Space/Time Requirements . . . . . 37
4.2.5 Restrictions Imposed in Processing Order . . . . . 37
4.3 Processor Dependencies (Previous PGEs, Ingest Data,..) . . . . . 37
4.3.1 Input Dataset Name (#1): preES-8 . . . . . 37
4.3.2 Alternate Dataset Name (#1): S-8 . . . . . 38
4.3.3 Input Dataset Name (#2): SNOW . . . . . 38
4.3.4 Input Dataset Name (#3): Spectral Response and Correction Coefficients . . . . . 39
4.4 Operating Procedures (Procedure for each part of the processor's elements) . . . . . 39
4.4.1 How to Generate the ASCII File and PCF . . . . . 39
4.4.2 How to Execute the Main-Processor . . . . . 40

# TABLE OF CONTENTS

Section Page


4.4.3 Special Case Considerations . . . . . 40
4.4.4 Special Reprocessing Instructions . . . . . 40
4.5 Execution Evaluation . . . . . 41
4.5.1 Exit Codes . . . . . 41
4.5.2 Screen Messages (Use Table format for large number of messages.) . . . . . 41
4.5.3 Log and Status Files Results (Include ALL Log Files) . . . . . 42
4.5.3.1 Report Log File: CER2.3P2_LogReport_$SS2_$PS2_$CC2.yyyymmdd . . . . . 42
4.5.3.2 Status Log File: CER2.3P2_LogStatus_$SS2_$PS2_$CC2.yyyymmdd . . . . . 42
4.5.3.3 User Log File: CER2.3P2_LogUser_$SS2_$PS2_$CC2.yyyymmdd . . . . . 42
4.5.4 Solutions to Possible Problems . . . . . 43
4.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing) . . . . . 43
4.6 Expected Output Dataset(s) . . . . . 43
4.7 Expected Temporary Files/Directories . . . . . 44
5.0 PGEName: CER2.4P1 . . . . . 45
5.1 PGE Details . . . . . 45
5.1.1 Responsible Persons . . . . . 45
5.1.2 E-mail Distribution List . . . . . 45
5.1.3 Parent PGE(s) . . . . . 45
5.1.4 Target PGE(s) . . . . . 45
5.2 Operating Environment . . . . . 46
5.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.) . . . . . 46
5.2.2 Environment Script Requirements . . . . . 46
5.2.3 Execution Frequency (daily,hourly,..) . . . . . 46
5.2.4 Memory/Disk Space/Time Requirements . . . . . 46
5.2.5 Restrictions Imposed in Processing Order . . . . . 47
5.3 Processor Dependencies (Previous PGEs, Ingest Data,..) . . . . . 47
5.3.1 Input Dataset Name (#1): Time dependent spectral response functions . . . . . 47
5.4 Operating Procedures (Procedure for each part of the processor's elements) . . . . . 48
5.4.1 How to Generate the ASCII File and PCF . . . . . 48

# TABLE OF CONTENTS

Section Page


5.4.2 How to Execute the Main-Processor . . . . . 48
5.4.3 Special Case Considerations . . . . . 49
5.4.4 Special Reprocessing Instructions . . . . . 49
5.5 Execution Evaluation . . . . . 49
5.5.1 Exit Codes . . . . . 49
5.5.2 Screen Messages (Use Table format for large number of messages) . . . 50
5.5.3 Log and Status Files Results (Include ALL Log Files) . . . . . 51
5.5.3.1 Report Log File: CER2.4P1_LogReport_$SS2_ $PS2_4_$CC2_4.yyyymmdd . . . . . 51
5.5.3.2 Status Log File: CER2.4P1_LogStatus_$SS2_ $PS2_4_$CC2_4.yyyymmdd . . . . . 51
5.5.3.3 User Log File: CER2.4P1_LogUser_$SS2_ $PS2_4_$CC2_4.yyyymmdd . . . . . 51
5.5.4 Solutions to Possible Problems . . . . . 51
5.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing) . . . . . 51
5.6 Expected Output Dataset(s) . . . . . 52
5.7 Expected Temporary Files/Directories . . . . . 53
References . . . . . 54
Appendix A Acronyms and Abbreviations . . . . . A-1
Appendix B Error Messages for Subsystem 2.0 . . . . . B-1
Appendix C Sample ASCII (PCFin) File Listing(s) for Subsystem 2.0 . . . . . C-1

# LIST OF TABLES

Table Page

Table 1-1. Subsystem Software Analysts Contacts for CER2.1P1 . . . . . 5
Table 1-2. Target PGEs after CER2.1P1 . . . . . 6
Table 1-3. Runtime Parameters for CER2.1P1 . . . . . 6
Table 1-4. Exit Codes for CER2.1P1 . . . . . 9
Table 1-5. Screen Messages for execution of CER2.1P1. . . . . 10
Table 1-6. Expected Output File Listing for CER2.1P1 . . . . . 11
Table 1-7. Temporary Files Listing for CER2.1P1 . . . . . 12
Table 2-1. Parent PGEs for CER2.2P1. . . . . 13
Table 2-2. Target PGEs after CER2.2P1 . . . . . 13
Table 2-3. Runtime Parameters for CER2.2P1 . . . . . 14
Table 2-4. Exit Codes for CER2.2P1 . . . . . 20
Table 2-5. Screen Messages for execution of CER2.2P1. . . . . 21
Table 2-6. Expected Output File Listing for CER2.2P1 . . . . . 23
Table 2-7. Temporary Files Listing for CER2.2P1 . . . . . 24
Table 3-1. Parent PGEs for CER2.3P1. . . . . 25
Table 3-2. Target PGEs after CER2.3P1 . . . . . 25
Table 3-3. Runtime Parameters for CER2.3P1 . . . . . 26
Table 3-4. Exit Codes for CER2.3P1 . . . . . 31
Table 3-5. Screen Messages for execution of CER2.3P1. . . . . 31
Table 3-6. Expected Output File Listing for CER2.3P1 . . . . . 33
Table 3-7. Temporary Files Listing for CER2.3P1 . . . . . 34
Table 4-1. Parent PGEs for CER2.3P2. . . . . 35
Table 4-2. Target PGEs after CER2.3P2 . . . . . 35
Table 4-3. Runtime Parameters for CER2.3P2 . . . . . 36
Table 4-4. Exit Codes for CER2.3P2 . . . . . 41
Table 4-5. Screen Messages for execution of CER2.3P2. . . . . 41
Table 4-6. Expected Output File Listing for CER2.3P2 . . . . . 43
Table 4-7. Temporary Files Listing for CER2.3P2 . . . . . 44
Table 5-1. Target PGEs after CER2.4P1 . . . . . 45
Table 5-2. Runtime Parameters for CER2.4P1 . . . . . 46
Table 5-3. Exit Codes for CER2.4P1 . . . . . 49
Table 5-4. Screen Messages for execution of CER2.4P1. . . . . 50
Table 5-5. Expected Output File Listing for CER2.4P1 . . . . . 52
Table 5-6. Temporary Files Listing for CER2.4P1 . . . . . 53
Table B-1. PGE CER2.1P1 Error Messages . . . . . B-2

# LIST OF TABLES

Table Page

Table B-2. PGEs CER2.2P1 Error Messages . . . . . B-4
Table B-3. PGEs CER2.3P1 - CER2.3P2 Error Messages . . . . . B-9
Table B-4. PGEs CER2.4P1 Error Messages . . . . . B-13

# Introduction

The Clouds and the Earth's Radiant Energy System (CERES) is a key component of the Earth Observing System (EOS) program. The CERES instrument provides radiometric measurements of the Earth's atmosphere from three broadband channels: a shortwave channel (0.3 - 5 µm), a total channel (0.3 - 200 µm), and an infrared window channel (8 - 12 µm). The CERES instruments are improved models of the Earth Radiation Budget Experiment (ERBE) scanner instruments, which operated from 1984 through 1990 on the National Aeronautics and Space Administration's (NASA) Earth Radiation Budget Satellite (ERBS) and on the National Oceanic and Atmospheric Administration's (NOAA) operational weather satellites NOAA-9 and NOAA-10. The strategy of flying instruments on Sun-synchronous, polar orbiting satellites, such as NOAA-9 and NOAA-10, simultaneously with instruments on satellites that have precessing orbits in lower inclinations, such as ERBS, was successfully developed in ERBE to reduce time sampling errors. CERES continues that strategy by flying instruments on the polar orbiting EOS platforms simultaneously with an instrument on the Tropical Rainfall Measuring Mission (TRMM) spacecraft, which has an orbital inclination of 35 degrees. In addition, to reduce the uncertainty in data interpretation and to improve the consistency between the cloud parameters and the radiation fields, CERES includes cloud imager data and other atmospheric parameters. The TRMM satellite carries one CERES instrument while the EOS satellites carry two CERES instruments, one operating in a fixed azimuth plane scanning mode (FAPS) for continuous Earth sampling and the other operating in a rotating azimuth plane scan mode (RAPS) for improved angular sampling.

## Document Overview

This document, *CERES ERBE-like Inversion to Instantaneous TOA Fluxes (Subsystem 2.0) Operator's Manual*, is part of the Release 3 CERES Subsystem 2.0 and 3.0 package provided to the Langley Atmospheric Sciences Data Center (ASDC). It provides a description of the CERES ERBE-like Subsystem 2.0 Release 3 software and explains the procedures for executing the software. A description of Acronyms and Abbreviations is provided in Appendix A, a list of PGE generated Error Messages is contained in Appendix B, and a Sample PCF ASCII Input File Listing is provided in Appendix C.

This document is organized as follows:

Introduction
Document Overview
Subsystem Overview
1.0 PGEName: CER2.1P1 - CERES ERBE-like Monthly Geo-Scene and Snow Map, and Longwave and Albedo Thresholds.
2.0 PGEName: CER2.2P1 - CERES ERBE-like Daily Inversion for a Single Instrument.
3.0 PGEName: CER2.3P1 - CERES ERBE-like Monthly Inversion for the First Day of the Next Month.
4.0 PGEName: CER2.3P2 - CERES ERBE-like Monthly Inversion for the Last Day of the Previous Month.

5.0 PGEName: CER2.4P1 - CERES ERBE-like Spectral Response Functions and Correction Coefficients.
References
Appendix A - Acronyms and Abbreviations
Appendix B - Error Messages
Appendix C - PCF ASCII Input File Listing

## Subsystem Overview

The ERBE-like software is divided into two subsystems; Subsystem 2.0 - ERBE-like Inversion, which processes daily data, and Subsystem 3.0 - ERBE-like Monthly Averaging, which processes once a month. The ERBE-like Subsystems 2.0 and 3.0 come from the ERBE Subsystems V and VI. Details concerning the conversion process from the ERBE to the CERES ERBE-like code may be found in the CERES Software Requirement Documents for Subsystem 2.0 and 3.0 (Reference 1).

### Subsystem 2.0 (ERBE-like Inversion)

The ERBE-like Inversion Subsystem calculates estimates of the radiant flux at the top-of-atmosphere (TOA) based on satellite altitude data from the Instrument Subsystem (1.0). This inversion process is dependent on several factors, including Earth surface features; the extent of cloudiness; and the relative geometry of the spacecraft, the Sun, and the measurement field-of-view (FOV). Each radiometric measurement is spectrally corrected to give an unfiltered measurement. The observed scene is determined by the ERBE scene identification algorithm based on these unfiltered measurements using angular distribution models and statistics provided by the CERES Science Team. Estimates of the radiant flux at the TOA are computed based on scene information, geometrical considerations, and the unfiltered measurements.

PGE CER2.1P1 generates a binary input file containing geo-scene types (including snow cover) and albedo and longwave threshold values used by the other ERBE-like Subsystem 2.0 PGEs. This PGE also generates geo-scene maps as color postscript files and as gif files for display over the Web.

PGE CER2.2P1 is the ERBE-like daily inversion main-processor. The binary ES-8 and EID-6 files and the ES-8 HDF-EOS archival product are produced. This PGE also generates monthly QC and ES-8 GIF files to support the ERBE-like Web applications.

PGEs CER2.3P1 and CER2.3P2 are used to process overlap data for a data month. CER2.3P1 processes data that are collected on the first day of a month but belong to the last day of the previous month. CER2.3P2 processes data that are collected on the last day of a month but belong to the first day of the next month.

PGE CER2.4P1 generates the Spectral Correction Coefficient day and night files containing the spectral response and spectral correction coefficients values used by the ERBE-like Subsystem 2.0 PGEs; CER2.2P1, CER2.3P1, and CER2.3P2.

The following table contains each PGE with its execution frequency, PGE dependencies (input requirements), target PGEs, and a short description.

## ERBE-like (Subsystems 2.0 and 3.0) Processing (FAPS+RAPS) Overview (1 of 2)

| PGE | Freq. | PGE Dependencies | Target PGEs | Description |
|---|---|---|---|---|
| CER2.1P1 | 1/month | Ingest Data | CER2.2P1<br>CER2.3P1<br>CER2.3P2 | This PGE is run after the end of the data month after all ingest data have arrived. |
| CER2.2P1 | 1/day (Quick Look, validation) | CER1.2P1 | N/A | This PGE is processed three times, the first time with composite snow. The output is viewed and deleted after the PGE is processed a second time with actual snow, see next item. |
| CER2.2P1 | 1/day (Baseline, validation) | CER1.2P1<br>CER2.1P1 | N/A | This PGE is processed a second time after the end of the data month with actual snow (output from 2.1P1). The output is used in spectral response function analysis, see next item. |
| CER2.2P1 | 1/day (for archival) | CER1.2P1<br>CER2.1P1<br>CER2.4P1 | CER3.1P1<br>CER3.2P2 | This PGE is processed a third time after the processing of the spectral correction coefficients. Actual snow (output from 2.1P1) and updated spectral correction coefficients (output from 2.4P1). Output from this process will be input to Subsystem 3.0. |
| CER2.3P1 | 1/month | CER1.2P1<br>CER2.1P1<br>CER2.4P1 | CER3.1P1 | This PGE creates an overlap data file from the first day of the next month. Actual snow of the current month and updated spectral correction coefficients of the current day is used. Ancillary input must be the same as used for the second processing of CER2.2P1. |
| CER2.3P2 | 1/month | CER1.2P1<br>CER2.1P1<br>CER2.4P1 | CER3.1P1 | This PGE creates an overlap data file from the last day of the previous month. Actual snow of the current month and updated spectral correction coefficients of the current day is used. Ancillary input must be the same as used for the second processing of CER2.2P1. |
| CER2.4P1 | 1/day | CER1.3P2 | CER2.2P1<br>CER2.3P1<br>CER2.3P2<br>CER4.5-6.1P2 | This PGE creates the spectral response and spectral correction coefficient values for the inversion process. |

## ERBE-like (Subsystems 2.0 and 3.0) Processing (FAPS+RAPS) Overview (2 of 2)

| PGE | Freq. | PGE Dependencies | Target PGEs | Description |
|---|---|---|---|---|
| Note: From this point on, the processors are considered as part of the Subsystem 3.0 process scenario. | | | | |
| CER3.1P1 | 1/month | CER2.2P1<br>CER2.3P1<br>CER2.3P2 | CER3.2P1<br>CER3.2P2 | Monthly Averaging. This PGE creates archival products ES-4 and ES-9. |
| CER3.2P1 | 1/month | CER3.1P1 | N/A | Multi-Instrument Monthly Averaging. This PGE creates archival products ES-4 and ES-9. |
| CER3.2P2 | 1/month | CER2.2P1<br>CER3.1P1 | N/A | Monthly Direct Comparison and Three Channel Inter-comparison plotting. |

Seven Product Generation Executives (PGEs) are used to run the ERBE-like software (Subsystems 2.0 and 3.0). This Operator's Manual describes the Subsystem 2.0 PGE procedures. The *CERES ERBE-like Averaging to Monthly TOA Fluxes (Subsystem 3.0) Operator's Manual* (Reference 2) is also available.

# 1.0 PGEName: CER2.1P1

**CERES ERBE-like Monthly Geo-Scene and Snow Map, and Longwave and Albedo Thresholds**

## 1.1 PGE Details

### 1.1.1 Responsible Persons

Table 1-1. Subsystem Software Analysts Contacts for CER2.1P1

| Item | Primary | Alternate |
|---|---|---|
| Contact Name | Edward A. Kizer | Dale R. Walikainen |
| Organization | SAIC | SAIC |
| Address | 1 Enterprise Parkway | 1 Enterprise Parkway |
| City | Hampton | Hampton |
| State | VA 23666 | VA 23666 |
| Phone | 827-4883 | 827-4687 |
| Fax | 825-4968 | 825-4968 |
| LaRC email | e.a.kizer@larc.nasa.gov | d.r.walikainen@larc.nasa.gov |

### 1.1.2 E-mail Distribution List

E-mail distribution list can be obtained from the primary contact listed in Table 1-1.

### 1.1.3 Parent PGE(s)

A parent PGE generates data for input to the current PGE, CER2.1P1. PGE CER2.1P1 is only dependent on outside data sources and has no parent PGE(s).

### 1.1.4 Target PGE(s)

A target PGE requires input data generated from the current PGE, CER2.1P1.

Table 1-2. Target PGEs after CER2.1P1

| PGEName | Description |
|---|---|
| CER2.2P1 | CERES ERBE-like Daily Inversion to Instantaneous TOA Fluxes Main-Processor for FAPS+RAPS data for a Single Instrument. |
| CER2.3P1 | CERES ERBE-like Monthly Inversion to Instantaneous TOA Fluxes Overlap-Processor for FAPS+RAPS data for a Single Instrument for the First Day of the Next Month. |
| CER2.3P2 | CERES ERBE-like Monthly Inversion to Instantaneous TOA Fluxes Overlap-Processor for FAPS+RAPS data for a Single Instrument for the Last Day of the Previous Month. |

## 1.2 Operating Environment

### 1.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.)

Table 1-3. Runtime Parameters for CER2.1P1

| Parameter[a] | Description | Valid Values |
|---|---|---|
| yyyy | 4-digit CERDataDateYear | >= 1984 |
| mm | 2-digit CERDataDateMonth | 01 .. 12 |

a. All character strings.

### 1.2.2 Environment Script Requirements

Refer to the CERES internal paper (Reference 3) for a detailed description of the CERES environment parameters. For the current values of the Sampling Strategy and Production Strategy variables listed below, see "CERES DMT to DAAC Processing Requests." (URL: http://asd-www.larc.nasa.gov/ceres/dmt2daac/)

One environment script is required. It is named '**ENVerbelike-env.csh**' and contains the following parameters:

SS2_1 - Sampling Strategy for CER2.1P1, see Production Request (Reference 4)
PS2_1 - Production Strategy for CER2.1P1, see Production Request (Reference 4)
CC2_1 - Configuration Code for CER2.1P1, see CM Database
SAT - Satellite, see Production Request (Reference 4)
IMAG - Image, see Production Request (Reference 4)
INST - Instrument, see Production Request (Reference 4)

### 1.2.3 Execution Frequency (daily,hourly,..)

**monthly (1/month)** - This PGE is to be processed once per month, when input is available.

### 1.2.4 Memory/Disk Space/Time Requirements

| | |
|---|---|
| Memory: | 97.5 MB |
| Disk Space: | 0.51 MB |
| Total Run Time: | 0:42 minutes |

### 1.2.5 Restrictions Imposed in Processing Order

PGE CER2.1P1 requires that the number of missing daily input files for the data month is no more than 10. If the required number of input files are not available, contact the Subsystem software analysts from Table 1-1.

## 1.3 Processor Dependencies (Previous PGEs, Ingest Data,..)

***Note: Include all required inputs such as .met files, header files, etc.***

### 1.3.1 Input Dataset Name (#1): NISE_SSMIF13

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

   **$CERESHOME/erbelike/data/input/NISE_SSMIF13_yyyymmdd.HDFEOS**

   **Where yyyy and mm are described in Table 1-3 and dd ranges from 01 to 31.**

   1. Mandatory/Optional: **Mandatory. The maximum number of missing files is 10 in a data month.**
   2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm.**
   3. Waiting Period: **Run PGE when data for the data month are available, if the minimum requirement is satisfied. (Typically, satisfying this requirement will take approximately 10 days after the end of the data month.)**

b. Source of Information (Source PGE name or Ingest Source):

   **Ingest Source - National Snow and Ice Data Center (NSIDC).**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Remove.**

e. Typical file size (MB): **2.1**

## 1.4 Operating Procedures (Procedure for each part of the processor's elements)

The production script, **CER2.1P1**, references a Process Control File (PCF) which contains the file names and paths for the PGE. This PCF is created by first sourcing the ERBE-like-specific environment script, **ENVerbelike-env.csh**, then executing an ASCII file and PCF generator, **gen_pcf.CER2.1P1**.

### 1.4.1 How to Generate the ASCII File and PCF

The ASCII file and PCF generator requires one command-line argument: data date (yyyymm) (see Table 1-3).

At the command-line (>) type:

> **> cd $CERESHOME/erbelike/data/scr**
> **> $CERESHOME/erbelike/bin/gen_pcf.CER2.1P1 yyyymm**

The following files are generated and located in **$CERESHOME/erbelike/rcf/pcf/**:

**CER2.1P1_PCFin_$SS2_1_$PS2_1_$CC2_1.yyyymm**
**CER2.1P1_PCF_$SS2_1_$PS2_1_$CC2_1.yyyymm**

### 1.4.2 How to Execute the Main-Processor

Clear the output directories of files previously generated from this PGE by executing script, **clr_dir.PGE2.1**, with the runtime parameter data date. Before running the program, make sure the executable, gen_snow.exe, is in the $CERESHOME/erbelike/bin directory. Execute the production script by typing the script name, **CER2.1P1**, followed by a string which designates the instance of the data. The string should be formatted, "Sampling Strategy"_"Production Strategy"_"Configuration Code"."DataDate". The date parameter is formatted, yyyymm, where yyyy is the data year and mm is the data month (see Table 1-3).

At the command-line (>) type:

> **> cd $CERESHOME/erbelike/data/scr**
> **> $CERESHOME/erbelike/bin/clr_dir.PGE2.1 yyyymm**
> **> $CERESHOME/erbelike/bin/CER2.1P1 $SS2_1_$PS2_1_$CC2_1.yyyymm**

### 1.4.3 Special Case Considerations

N/A, at this time. Special case considerations will be handled on a case-by-case basis, where instructions will accompany each special request.

### 1.4.4 Special Reprocessing Instructions

1. All output files are opened with Status = NEW in the CER2.1P1 software. These files must be removed before rerunning these procedures. A script, which removes PGE created files, **clr_dir.PGE2.1**, is located in directory $CERESHOME/erbelike/bin. Using data date as a command line argument:

   > **$CERESHOME/erbelike/bin/clr_dir.PGE2.1 yyyymm**

2. See reprocessing requirements in "CERES DMT to DAAC Processing Requests" available on the Web at: http://asd-www.larc.nasa.gov/ceres/docs.html.

## 1.5 Execution Evaluation

### 1.5.1 Exit Codes

The processor CER2.1P1 terminates using the CERES-defined EXIT CODES for the Langley TRMM Information System (LaTIS) as seen in Table 1-4. Other exit codes may appear from the program, which may be the result of a system, compiler, or Toolkit related error. In these cases, contact the responsible person for assistance (see Table 1-1).

Table 1-4. Exit Codes for CER2.1P1

| Exit Code | Definition | Action |
|---|---|---|
| 0 | Normal Exit | Proceed normally |
| 198 | Fatal | "PCF: CER2.1P1_PCF_$SS2_1_$PS2_1_$CC2_1.yyyymm DoesNOT exist" Inform the primary contact in Table 1-1. |
| 202 | Fatal | Check the Log files, inform the primary contact from Table 1-1, and take the appropriate action (see Appendix B). |
| 203 | Fatal | Check the Log files, inform the primary contact from Table 1-1, and take the appropriate action (see Appendix B). |

### 1.5.2 Screen Messages (Use Table format for large number of messages)

Table 1-5. Screen Messages for execution of CER2.1P1

| Message | Definition/Action |
|---|---|
| Cannot access <filename>: No such file or directory | From the clear directory script, clr_dir.PGE2.1, as a part of the Main-Processor. This message occurs when the script tries to remove an old output file that does not exist. Proceed normally. |
| PCF:<br>CER2.1P1_PCF_$SS2_1_$PS2_1_$CC2_1.yyyymm<br>DoesNOT exist<br>Exit Status = 198 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.1P1<br>CER2.1P1_PCF_$SS2_1_$PS2_1_$CC2_1.yyyymm<br>UNSUCCESSFULLY terminated in gen_snow<br>Exit Status = 201 | From running the production script, CER2.1P1, this message written to the screen signifies a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.1P1<br>CER2.1P1_PCF_$SS2_1_$PS2_1_$CC2_1.yyyymm<br>UNSUCCESSFULLY terminated in ps_to_gif<br>Exit Status = 202 | From running the production script, CER2.1P1, this message written to the screen signifies a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.1P1<br>CER2.1P1_PCF_$SS2_1_$PS2_1_$CC2_1.yyyymm<br>UNSUCCESSFULLY terminated in idl<br>Exit Status = 203 | From running the production script, CER2.1P1, this message written to the screen signifies a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |

### 1.5.3 Log and Status Files Results (Include ALL Log Files)

The Log files contain all error and/or status messages produced by the PGE. The files are located in the directory: **$CERESHOME/erbelike/data/runlogs**.

#### 1.5.3.1 Report Log File: CER2.1P1_LogReport_$SS2_1_$PS2_1_$CC2_1.yyyymm

The Report Log File contains the PGE CER2.1P1 generated messages. These messages may be strictly informative (Error Type = Status or Warning) or may indicate a fatal condition that results in premature PGE termination (Error Type = Fatal). A list of these messages is contained in Appendix B.

#### 1.5.3.2 Status Log File: CER2.1P1_LogStatus_$SS2_1_$PS2_1_$CC2_1.yyyymm

The Status Log File contains all messages created by the Toolkit. If an abnormal exit is encountered by the PGE, this file should be examined for '_F_', fatal message type. The responsible person should be advised (see Table 1-1).

#### 1.5.3.3 User Log File: CER2.1P1_LogUser_$SS2_1_$PS2_1_$CC2_1.yyyymm

The User Log File is not used at this time, but exists to satisfy the Toolkit requirements. Typically the '_U_' and '_N_' (User information and Notice) will be written to the User Log File and the Status Log File.

### 1.5.4 Solutions to Possible Problems

If problems occur, consult the primary contact in Table 1-1.

### 1.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing)

a. Subsystem Termination

   All output files are opened with status "NEW". If files exist, the program will terminate.

b. Target PGE Termination

   If more than 10 days of snow data are not available for the data month, the program will terminate and the target PGEs should not run. Target PGEs should not be processed in instances of PGE failure and/or non-zero exit codes.

## 1.6 Expected Output Dataset(s)

(Note: Include all expected Web files.)
The expected output datasets are listed below for each instance of the PGE. This PGE is expected to run once per month.

Table 1-6. Expected Output File Listing for CER2.1P1 (1 of 2)

| File Name[a]/Directory | m/o | File Size (MB) | Freq/ PGE | Target PGE | Destination[b] |
|---|---|---|---|---|---|
| CER2.1P1_PCF_$SS2_1_$PS2_1_$CC2_1.yyyymm @($CERESHOME/erbelike/data/runlogs) | m | 0.012 | 1/month | N/A | Archive rm |
| CER2.1P1_PCFin_$SS2_1_$PS2_1_$CC2_1.yyyymm @($CERESHOME/erbelike/data/runlogs) | m | 0.004 | 1/month | N/A | Archive rm |
| CER2.1P1_LogReport_$SS2_1_$PS2_1_$CC2_1.yyyymm @($CERESHOME/erbelike/data/runlogs) | m | 0.001 | 1/month | N/A | Archive rm |
| CER2.1P1_LogStatus_$SS2_1_$PS2_1_$CC2_1.yyyymm @($CERESHOME/erbelike/data/runlogs) | m | 0.003 | 1/month | N/A | Archive rm |
| CER2.1P1_LogUser_$SS2_1_$PS2_1_$CC2_1.yyyymm @($CERESHOME/erbelike/data/runlogs) | m | 0.001 | 1/month | N/A | Archive rm |

Table 1-6. Expected Output File Listing for CER2.1P1 (2 of 2)

| File Name[a]/Directory | m/o | File Size (MB) | Freq/ PGE | Target PGE | Destination[b] |
|---|---|---|---|---|---|
| CER_SNOW_$SS2_1_$PS2_1_$CC2_1.yyyymm (.met) @($CERESHOME/erbelike/data/ancillary/dynamic) | m | 0.031 | 1/month | CER2.2P1 CER2.3P1 CER2.3P2 | Archive |
| CER_CQCR_$SS2_1_$PS2_1_$CC2_1.yyyymm (.met) @($CERESHOME/erbelike/data/out_comp/data/snow) | m | 0.019 | 1/month | N/A | Archive rm |
| CEREScqcrw_yyyymm.txt @($CERESHOME/erbelike/Web/qc/snow) | m | 0.019 | 1/month | N/A | /QA, permanent, **NO ARCHIVE** |
| CERESweb_yyyymm.map @($CERESHOME/erbelike/Web/snow/data) | o | 0.011 | 1/month | N/A | /QA, permanent, **NO ARCHIVE** |
| CERESfmt_yyyymm.map @($CERESHOME/erbelike/Web/snow/data) | o | 0.013 | 1/month | N/A | /QA, permanent, **NO ARCHIVE** |
| CERESscr_yyyymm.gif @($CERESHOME/erbelike/Web/snow/data) | o | 0.390 | 1/month | N/A | /QA, permanent, **NO ARCHIVE** |

a. See Section 1.2 for information on variable data values.
If "(.met)" is written next to an expected output filename, then the metatdata file with the identical filename and .met extension must exist.

b. Note:
/QA - File is to be written to the DAAC designated /QA directory
rm - remove
yyyy - 4-digit year (See Runtime Parameters Table 1-3)
mm - 2-digit month {valid values: 01 .. 12} (See Runtime Parameters Table 1-3)
m - mandatory output
o - optional output

## 1.7 Expected Temporary Files/Directories

Table 1-7. Temporary Files Listing for CER2.1P1

| Directory[a] | File Name |
|---|---|
| $CERESHOME/erbelike/data/scr/ CER2.1P1_$SS2_1_$PS2_1_$CC2_1.yyyymm | TempENV.dat |
| $CERESHOME/erbelike/data/scr/ CER2.1P1_$SS2_1_$PS2_1_$CC2_1.yyyymm | TempSNOW.ps |
| $CERESHOME/erbelike/data/scr/ CER2.1P1_$SS2_1_$PS2_1_$CC2_1.yyyymm | Mail_2.1p1.txt |

a. See Section 1.2 for information on variable data values.

# 2.0 PGEName: CER2.2P1

**CERES ERBE-like Daily Inversion for a Single Instrument.**

## 2.1 PGE Details

### 2.1.1 Responsible Persons

See Table 1-1, Subsystem Software Analysts Contacts.

### 2.1.2 E-mail Distribution List

E-mail distribution list can be obtained from the primary contact listed in Table 1-1.

### 2.1.3 Parent PGE(s)

A parent PGE generates data for input to the current PGE, CER2.2P1.

Table 2-1. Parent PGEs for CER2.2P1

| PGEName | Description |
|---|---|
| CER1.2P1 | CERES BDS to Pre-ES8 conversion post-processor. |
| CER2.1P1 | CERES ERBE-like Monthly Geo-Scene and Snow Map, and Longwave Flux and Albedo Thresholds. |
| CER2.4P1 | CERES ERBE-like Spectral Response Functions and Correction Coefficients. |

### 2.1.4 Target PGE(s)

A target PGE requires input data generated from the current PGE, CER2.2P1.

Table 2-2. Target PGEs after CER2.2P1

| PGEName | Description |
|---|---|
| CER3.1P1 | CERES ERBE-like Monthly TOA Flux Averaging Main-Processor for FAPS+RAPS data for a Single Instrument. |
| CER3.2P2 | CERES ERBE-like Monthly Direct Comparison and Three Channel Inter-comparison Analyses. |

## 2.2 Operating Environment

### 2.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.)

Table 2-3. Runtime Parameters for CER2.2P1

| Parameter[a] | Description | Valid Values |
|---|---|---|
| yyyy | 4-digit CERDataDateYear | >= 1984 |
| mm | 2-digit CERDataDateMonth | 01 .. 12 |
| dd | 2-digit CERDataDateDay | 01 .. 31 |
| snow | Type of input snow file "Actual" or "Composite" | "A" or "C" |
| adm | Original or New Angular Directional Model structure | "F" or "N" |
| spcor | Original, Slope Intercept Spectral Correction Algorithm, or Instrument Team's modified input for the Slope Intercept Spectral Correction Algorithm. | "F", "N", "D" or "M" |
| swoff | Type of SW Offset "Day/Night", "Thermal" or "No offsets" | "D", "T", or "Z" |

a. All character strings.

### 2.2.2 Environment Script Requirements

Refer to the CERES internal paper (Reference 3) for a detailed description of the CERES environment parameters. For the current values of the Sampling Strategy and Production Strategy variables listed below, see "CERES DMT to DAAC Processing Requests." (URL: http://asd-www.larc.nasa.gov/ceres/dmt2daac/)

One environment script is required. It is named '**ENVerbelike-env.csh**' and contains the following parameters:

SS1 - Sampling Strategy for CER1.2P1, see Production Request (Reference 4)
SS2_1 - Sampling Strategy for CER2.1P1, see Production Request (Reference 4)
SS2 - Sampling Strategy for CER2.2P1, see Production Request (Reference 4)
PS1 - Production Strategy for CER1.2P1, see Production Request (Reference 4)
PS2_1 - Production Strategy for CER2.1P1, see Production Request (Reference 4)
PS2_4 - Production Strategy for CER2.4P1, see Production Request (Reference 4)
PS2 - Production Strategy for CER2.2P1, see Production Request (Reference 4)
CC1_2 - Configuration Code for CER1.2P1, see CM Database
CC2_1 - Configuration Code for CER2.1P1, see CM Database
CC2_4 - Configuration Code for CER2.4P1, see CM Database
CC2 - Configuration Code for CER2.2P1, see CM Database
SAT - Satellite, see Production Request (Reference 4)
IMAG - Imager, see Production Request (Reference 4)
INST - Instrument, see Production Request (Reference 4)

### 2.2.3 Execution Frequency (daily,hourly,..)

**daily (2/day)** - This PGE is to be processed twice per data day, following the guidelines described in Section 2.2.5, Restrictions Imposed in Processing Order.

### 2.2.4 Memory/Disk Space/Time Requirements

| | |
|---|---|
| Memory: | 546 MB |
| Disk Space: | 800 MB |
| Total Run Time: | 8:15 minutes |

### 2.2.5 Restrictions Imposed in Processing Order

PGE CER2.2P1 will be executed three times for each data day. It will be run first with "composite snow" for validation processing. This processing is performed to get a quick-look at the data for validation purposes before the actual snow data for the month is available. When the actual snow data becomes available, the month is rerun using the actual snow data. When the spectral response function and correction coefficient input data becomes available, the month is rerun again using the spectral response function and correction coefficient data. The operating procedures in Section 2.4.1 and Section 2.4.2 will be used for processing with either set of snow data and either set of spectral response function and correction coefficient input data.

Composite Snow Processing:

The CERES Science Team has requested this process be run daily with the appropriate composite snow ancillary file, 'SNOW_COMPOSITE_mm.19980130[1]', as soon as CER1.2P1 is run and a new preES-8 file is created. The value of the runtime parameter 'snow' is set to "C", and the Production Strategy (PS2) is set to include the annotation 'QC', which will be reflected in the output file names. There is no target PGE for this process. The output files from Composite Snow Processing are used for validation purposes only and are deleted as soon as Actual Snow Processing is completed for the entire data month.

Actual Snow Processing:

PGE CER2.1P1 must generate the actual snow data for the current data month (see input requirement Section 2.3.3) prior to this process. The value of the runtime parameter 'snow' is set to "A", and the Production Strategy (PS2) is unchanged from the value initially set in the environment script (Section 2.2.2). Once Actual Snow Processing is run daily for the entire month of data, the output files from Composite Snow Processing are deleted. The target PGE is CER3.1P1.

1. mm = 01 .. 12 for each data month, and
19980130 = the generation date of the ancillary file.

Angular Direction Model Processing:

The value of the runtime parameter 'adm' is set to "F" to process the original ADM structure currently run in CERES data processing. The value of the runtime parameter 'adm' is set to "N" to process the newer ADM structure currently run in ERBE data reprocessing.

Spectral Correction Algorithm Processing:

The value of the runtime parameter 'spcor' is set to "F" to process the original Spectral Correction Algorithm currently run in ERBE data reprocessing. The value of the runtime parameter 'spcor' is set to "N" to process the newer Slope Intercept Spectral Correction Algorithm currently run in CERES data processing. The value of the runtime parameter 'spcor' is set to "D" to process the daily Slope Intercept Spectral Correction Algorithm using the daily Spectral Response Function and Correction Coefficient Files generated by PGE CER2.4P1. The value of the runtime parameter 'spcor' is set to "M" to process the monthly Slope Intercept Spectral Correction Algorithm using monthly Spectral Response Function and Correction Coefficient Files generated by PGE CER2.4P1. The monthly file is represented by the daily Spectral Response Function and Correction Coefficient file for the 15th of the runtime parameter 'mm'.

SW Offset Processing:

The value of the runtime parameter 'swoff' is set to "D" to apply the day/night SW offsets currently run in ERBE data reprocessing. The value of the runtime parameter 'swoff' is set to "T" to apply the thermal offset applied the Slope Intercept Spectral Correction Algorithm currently run in CERES data processing. The value of the runtime parameter 'swoff' is set to "Z" to not apply any SW offsets.

## 2.3 Processor Dependencies (Previous PGEs, Ingest Data,..)

**None. Process when Input Data are available.**

### 2.3.1 Input Dataset Name (#1): preES-8

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/instrument/data/out_comp/**
**CER_PRES8_$SS1_$PS1_$CC1_2.yyyymmdd**

1. Mandatory/Optional: **This file is mandatory.**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
3. Waiting Period: **None, process when all input data are available (see** Section 2.2.5**).**

b. Source of Information (Source is PGE name or Ingest Source):

**Source PGE: CER1.2P1**

c. Alternate Data Set, if one exists (maximum waiting period):

**Reprocessing ERBE data using the ERBE S-8 (see Section 2.3.2).**

d. File Disposition after successful execution: **Do not remove until monthly processing (Subsystem 3.0) is complete. The file for "the last day of the month" cannot be removed until the monthly processing of the following month is complete.**

e. Typical file size (MB): **283**

### 2.3.2 Alternate Dataset Name (#1): S-8

**Reprocess ERBE data from November 5, 1984 through February 28, 1990**

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/instrument/data/out_comp/s8_yymmdd_sc**
where, sc is the satellite number: "1" for NOAA9, "2" for ERBS, or "3" for NOAA10.

1. Mandatory/Optional: **This file is mandatory.**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
3. Waiting Period: **None, process when all input data are available (see Section 2.2.5).**

b. Source of Information (Source is PGE name or Ingest Source):

**Ingest Source: LaTIS.**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Do not remove until monthly processing (Subsystem 3.0) is complete. The file for "the last day of the month" cannot be removed until the monthly processing of the following month is complete.**

e. Typical file size (MB): **37**

### 2.3.3 Input Dataset Name (#2): SNOW

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/erbelike/data/ancillary/dynamic/**
**CER_SNOW_$SS2_1_$PS2_1_$CC2_1.yyyymm**

1. Mandatory/Optional: **This file is mandatory for Actual Snow Processing (see Section 2.2.5).**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm.**
3. Waiting Period: **One month, process when all input data are available.**

b. Source of Information (Source is PGE name or Ingest Source):

**Source PGE: CER2.1P1**

c. Alternate Data Set, if one exists (maximum waiting period): **The ancillary input file 'SNOW_COMPOSITE_mm.19980130' is used for Composite Snow Processing until the actual snow data file is generated (see** Section 2.2.5**).**

d. File Disposition after successful execution: **Do not remove.**

e. Typical file size (MB): **.03**

### 2.3.4 Input Dataset Name (#3): Spectral Response and Correction Coefficients

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/erbelike/data/ancillary/dynamic/**
**CER_SCCD_$SS2_$PS2_4_$CC2_4.yyyymmdd**
**CER_SCCN_$SS2_$PS2_4_$CC2_4.yyyymmdd**

1. Mandatory/Optional: **This file is mandatory for final processing (see** Section 2.2.5**).**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd. Note: If the runtime parameter, spcor, is equal to "M", then the data date is set to represent the 15th of the month, yyyymm15.**
3. Waiting Period: **One month, process when all input data are available.**

b. Source of Information (Source is PGE name or Ingest Source):

**Source PGE: CER2.4P1**

c. Alternate Data Set, if one exists (maximum waiting period): **The CERESlib data files 'ceres_SI_$instr_day.20020328' and 'ceres_SI_$instr_night.20020328' are used for Baseline Processing until the Spectral Response Function and Correction Coefficient data files are generated (see** Section 2.2.5**), where $instr is equal to the environment variable INST (see** Section 2.2.1**).**

d. File Disposition after successful execution: **Do not remove.**

e. Typical file size (MB): **.55, and .02**

## 2.4 Operating Procedures (Procedure for each part of the processor's elements)

The production script, **CER2.2P1**, references a Process Control File (PCF) which contains the file names and paths for the PGE. This PCF is created by first sourcing the ERBE-like-specific environment script, **ENVerbelike-env.csh**, then executing an ASCII file and PCF generator, **gen_pcf.CER2.2**.

### 2.4.1 How to Generate the ASCII File and PCF

The ASCII file and PCF generator requires five command-line arguments: data date (yyyymmdd), the snow file parameter (either Actual (A) or Composite (C)), ADM structure (either Original (F) or New (N)), Spectral Correction Algorithm (either Original (F), Slope Intercept Method (N), or Slope Intercept Method using the daily Spectral Response Function and Correction Coefficient Files generated by PGE CER2.4P1 (D)), and SW offsets (either day/night (D), thermal SW offsets (T), or no offsets (Z)) (see Table 2-3).

At the command-line (>) type:

**> cd $CERESHOME/erbelike/data/scr**
**> source $CERESHOME/erbelike/bin/ENVerbelike-env.csh**
**> $CERESHOME/erbelike/bin/gen_pcf.CER2.2 yyyymmdd snow adm spcor swoff**

The following files are generated and located in **$CERESHOME/erbelike/rcf/pcf/**:

**CER2.2P1_PCFin_$SS2_$PS2_$CC2.yyyymmdd**
**CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd**

### 2.4.2 How to Execute the Main-Processor

Clear the output directories of files previously generated from this PGE by executing script, **clr_dir.PGE2**, with the runtime parameter data date. Before running the program, make sure the executables (pre_es8.exe, inv.exe, gen_es8hdf.exe and read_qc.exe) are in the $CERESHOME/erbelike/bin directory. Execute the production script by typing the script name, **CER2.2P1**, followed by a string which designates the instance of the data. The string should be formatted, "Sampling Strategy"_"Production Strategy"_"Configuration Code"."DataDate". The date parameter is formatted, yyyymmdd, where yyyy is the data year, mm is the data month, and dd is the data day (see Table 2-3).

At the command-line (>) type:

**> cd $CERESHOME/erbelike/data/scr**
**> $CERESHOME/erbelike/bin/clr_dir.PGE2 yyyymmdd**
**> $CERESHOME/erbelike/bin/CER2.2P1 $SS2_$PS2_$CC2.yyyymmdd**

### 2.4.3 Special Case Considerations

Refer to Section 2.2.5, Restrictions Imposed in Processing Order.

### 2.4.4 Special Reprocessing Instructions

1. All output files are opened with Status = NEW in the CER2.2P1 software. These files must be removed before rerunning these procedures. A script, which removes PGE created files, **clr_dir.PGE2**, is located in directory $CERESHOME/erbelike/bin. Using data date as a command line argument:

   > **$CERESHOME/erbelike/bin/clr_dir.PGE2 yyyymmdd**

2. See reprocessing requirements in "CERES DMT to DAAC Processing Requests" available on the Web at: http://asd-www.larc.nasa.gov/ceres/docs.html.

## 2.5 Execution Evaluation

### 2.5.1 Exit Codes

The processor CER2.2P1 terminates using the CERES-defined EXIT CODES for the Langley TRMM Information System (LaTIS) as seen in Table 2-5. Other Exit Codes may appear from the program, which may be the result of a system, compiler, or Toolkit related error. In these cases, contact the responsible person for assistance (see Table 1-1).

Table 2-4. Exit Codes for CER2.2P1 (1 of 2)

| Exit Code | Definition | Action |
|---|---|---|
| 0 | Normal Exit | Proceed normally |
| 198 | Fatal | "PCF: CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd Does-NOT exist" Inform the primary contact in Table 1-1. |
| 199 | Fatal | "CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in pres8 conversion" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 200 | Fatal | "CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in inversion" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 201 | Fatal | "CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in es8hdf" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 202 | Fatal | "CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in plot_qc" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |

Table 2-4. Exit Codes for CER2.2P1 (2 of 2)

| Exit Code | Definition | Action |
|---|---|---|
| 203 | Fatal | "CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in plot_es8" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 204 | Fatal | "CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in qc checker" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 210 | Fatal | Unsuccessful termination in GenEs8SenID<br>Inform the primary contact from Table 1-1 |
| 211 | Fatal | Unsuccessful termination in GenEs8Ppm<br>Inform the primary contact from Table 1-1 |
| 212 | Fatal | Unsuccessful termination in GenEs8Ppm - too few colors. Inform the primary contact from Table 1-1 |
| 213 | Fatal | Unsuccessful termination in ppmtogif.<br>Inform the primary contact from Table 1-1 |
| 214 | Fatal | Unsuccessful termination in giftrans.<br>Inform the primary contact from Table 1-1 |
| 215 | Fatal | Non-existent or zero-sized GIF file(s) found<br>See Section 2.5.4 |

### 2.5.2 Screen Messages (Use Table format for large number of messages)

Table 2-5. Screen Messages for execution of CER2.2P1 (1 of 2)

| Exit Code | Definition |
|---|---|
| PCF: CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd DoesNOT exist<br>Exit Status = 198 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in pres8 conversion<br>Exit Status = 199 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in inversion<br>Exit Status = 200 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |

Table 2-5. Screen Messages for execution of CER2.2P1 (2 of 2)

| Exit Code | Definition |
|---|---|
| CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in es8hdf Exit Status = 201 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in plot_qc Exit Status = 202 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in plot_es8 Exit Status = 203 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.2P1 CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in qc checker Exit Status = 204 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |

### 2.5.3 Log and Status Files Results (Include ALL Log Files)

The Log files contain all error and/or status messages produced by the PGE. The files are located in the directory: **$CERESHOME/erbelike/data/runlogs**.

#### 2.5.3.1 Report Log File: CER2.2P1_LogReport_$SS2_$PS2_$CC2.yyyymmdd

The Report Log File contains the PGE CER2.2P1 generated messages. These messages may be strictly informative (Error Type = Status or Warning) or may indicate a fatal condition that results in premature PGE termination (Error Type = Fatal). A comprehensive list of these messages, that can be generated during the execution of the PGE, is contained in Appendix B.

#### 2.5.3.2 Status Log File: CER2.2P1_LogStatus_$SS2_$PS2_$CC2.yyyymmdd

The Status Log File contains all messages created by the Toolkit. If an abnormal exit is encountered by the PGE, this file should be examined for '_F_', fatal message type. The responsible person should be advised (see Table 1-1).

#### 2.5.3.3 User Log File: CER2.2P1_LogUser_$SS2_$PS2_$CC2.yyyymmdd

The User Log File is not used at this time, but exists to satisfy the Toolkit requirements. Typically the '_U_' and '_N_' (User information and Notice) will be written to the User Log File and the Status Log File.

### 2.5.4 Solutions to Possible Problems

If exit code 215 is encountered, then one or more zero length gif file have been created.

The operator can regenerate all of the 'gif' files associated with an ES-8 by executing the following command:

**> $CERESHOME/erbelike/bin/plot_es8 CER_ES8B_$SS2_$PS2_$CC2.yyyymmdd**

where, $SS2, $PS2, $CC2, yyyy, mm, dd, are the respective Environment and Runtime parameters (see Section 2.2.1 and Section 2.2.2).

### 2.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing)

a. Subsystem Termination

Please refer to Appendix B for a descriptive list of all errors and the result of those errors.

b. Target PGE Termination

Please refer to Appendix B for a descriptive list of all errors and the result of those errors. If .met files have not been created, the target PGEs should not run. Target PGEs should not be processed in instances of PGE failure.

## 2.6 Expected Output Dataset(s)

(Note: Include all expected Web files.)
The expected output datasets are listed below for each instance of the PGE. The PGE will be run once per day with composite snow and again with actual snow data.

Table 2-6. Expected Output File Listing for CER2.2P1 (1 of 2)

| File Name[a]/Directory | m/o[b] | File Size (MB) | Freq/PGE | Target PGE | Destination[c] |
|---|---|---|---|---|---|
| CER2.2P1_PCF_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.032 | 1/day | N/A | Archive rm |
| CER2.2P1_PCFin_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.003 | 1/day | N/A | Archive rm |
| CER2.2P1_LogReport_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.012 | 1/day | N/A | Archive rm |
| CER2.2P1_LogStatus_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.007 | 1/day | N/A | Archive rm |
| CER2.2P1_LogUser_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.001 | 1/day | N/A | Archive rm |

Table 2-6. Expected Output File Listing for CER2.2P1 (2 of 2)

| File Name[a]/Directory | m/o[b] | File Size (MB) | Freq/PGE | Target PGE | Destination[c] |
|---|---|---|---|---|---|
| CER_CQCI_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | m | 0.113 | 1/day | N/A | Archive rm |
| CER_EID6_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | m | 11.9 | 1/day | CER3.1P1 | Archive |
| CER_ES8B_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | m | 490 | 1/day | N/A | Archive rm |
| CER_ES8N_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | m | 3.56 | 1/day | CER3.2P2 | Archive |
| CER_ES8_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | m | 293 | 1/day | N/A | Archive rm |
| CER_CMSG_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/runlogs) | m | 0.015 | 1/day | N/A | Archive rm |
| CER_CQCIM_$SS2.yyyymm @($CERESHOME/erbelike/Web/qc/inv) | m | .11 | 1/month | N/A | /QA, permanent, **NO ARCHIVE** |
| ES8_yyyymmdd_i_jk.gif @($CERESHOME/erbelike/Web/graphics/ES8/gif/ ES8_yyyymm_i/ES8_yyyymmdd_i | m | 0.07 | 16/day | N/A | /QA, permanent, **NO ARCHIVE** |
| ES8_yyyymmdd_i_9.gif @($CERESHOME/erbelike/Web/graphics/ES8/gif/ ES8_yyyymm_i/ES8_yyyymmdd_i | m | 0.07 | 1/day | N/A | /QA, permanent, **NO ARCHIVE** |

a. See Section 2.2 for information on variable data values.
If "(.met)" is written next to an expected output filename, then the metatdata file with the identical filename and .met extension must exist.
Note: yyyy - 4-digit year (See Runtime Parameters Table 2-3)
mm - 2-digit month {valid values: 01 .. 12} (See Runtime Parameters Table 2-3)
dd - 2-digit day {valid values: 01 .. 31} (See Runtime Parameters Table 2-3)
i - instrument ID (valid values: 1,2,3,4,or 5)
j - plot number (valid value: 1...8)
k - color bar (valid value: 1,2)
b. Note: m - mandatory output
o - optional output
c. Note: /QA - File is to be written to the DAAC designated /QA directory
rm - remove

## 2.7 Expected Temporary Files/Directories.

Table 2-7. Temporary Files Listing for CER2.2P1

| Directory | File Name |
|---|---|
| $CERESHOME/erbelike/data/runlogs | ShmMem |

# 3.0 PGEName: CER2.3P1

**CERES ERBE-like Monthly Inversion for the First Day of the Next Month.**
Note: This PGE is run prior to PGE CER3.1P1 if there is input data from the first day of the next month.

## 3.1 PGE Details

### 3.1.1 Responsible Persons

See Table 1-1, Subsystem Software Analysts Contacts.

### 3.1.2 E-mail Distribution List

E-mail distribution list can be obtained from the primary contact listed in Table 1-1.

### 3.1.3 Parent PGE(s)

A parent PGE generates data for input to the current PGE, CER2.3P1.

Table 3-1. Parent PGEs for CER2.3P1

| PGEName | Description |
|---|---|
| CER1.2P1 | CERES BDS to Pre-ES8 conversion post-processor. |
| CER2.1P1 | CERES ERBE-like Monthly Geo-Scene and Snow Map, and Longwave Flux and Albedo Thresholds. |
| CER2.4P1 | CERES ERBE-like Spectral Response Functions and Correction Coefficients. |

### 3.1.4 Target PGE(s)

A target PGE requires input data generated from the current PGE, CER2.3P1.

Table 3-2. Target PGEs after CER2.3P1

| PGEName | Description |
|---|---|
| CER3.1P1 | CERES ERBE-like Monthly TOA Flux Averaging Main-Processor for FAPS+RAPS data for a Single Instrument. |

## 3.2 Operating Environment

### 3.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.)

The runtime parameters of PGE CER2.3P1 are relative to a target processing month in that for a given month, PGE CER2.3P1 supplies overlap data from the first day of the month after the target processing month. Therefore, where the descriptions "CERDataDateYear" and "CERDataDateMonth" are used, these descriptions will refer to the month and year of data for the target processing month.

Table 3-3. Runtime Parameters for CER2.3P1

| Parameter[a] | Description | Valid Values |
|---|---|---|
| yyyy | 4-digit Year corresponding to the month after the CERDataDateMonth | >= 1984 |
| mm | 2-digit Month after CERDataDateMonth | 01 .. 12 |
| dd | First day (2-digit) of the month after CERDataDateMonth | 01 |
| snow | Type of input snow file "Actual" | "A" or "C" |
| adm | Original or New Angular Directional Model structure | "F" or "N" |
| spcor | Original, Slope Intercept Spectral Correction Algorithm, or Instrument Team's modified input for the Slope Intercept Spectral Correction Algorithm. | "F", "N", "D" or "M" |
| swoff | Type of SW Offset "Day/Night", "Thermal" or "No offsets" | "D", "T", or "Z" |

a. All character strings.

### 3.2.2 Environment Script Requirements

Refer to the CERES internal paper (Reference 3) for a detailed description of the CERES environment parameters. For the current values of the Sampling Strategy and Production Strategy variables listed below, see "CERES DMT to DAAC Processing Request." (URL: http://asd-www.larc.nasa.gov/ceres/dmt2daac/)

One environment script is required. It is named '**ENVerbelike-env.csh**' and contains the following parameters:

SS1 - Sampling Strategy for CER1.2P1, see Production Request (Reference 4)
SS2_1 - Sampling Strategy for CER2.1P1, see Production Request (Reference 4)
SS2 - Sampling Strategy for CER2.2P1, see Production Request (Reference 4)
PS1 - Production Strategy for CER1.2P1, see Production Request (Reference 4)
PS2_1 - Production Strategy for CER2.1P1, see Production Request (Reference 4)
PS2_4 - Production Strategy for CER2.4P1, see Production Request (Reference 4)
PS2 - Production Strategy for CER2.2P1, see Production Request (Reference 4)

CC1_2 - Configuration Code for CER1.2P1, see CM Database
CC2_1 - Configuration Code for CER2.1P1, see CM Database
CC2_4 - Configuration Code for CER2.4P1, see CM Database
CC2 - Configuration Code for CER2.2P1, see CM Database
SAT - Satellite, see Production Request (Reference 4)
IMAG - Imager, see Production Request (Reference 4)
INST - Instrument, see Production Request (Reference 4)

### 3.2.3 Execution Frequency (daily,hourly,..)

**monthly (1/month)** - This PGE, along with PGE CER2.3P2, is to be processed once per month, immediately before PGE CER3.1P1.

### 3.2.4 Memory/Disk Space/Time Requirements

| | |
|---|---|
| Memory: | 5.04 MB |
| Disk Space: | 13 MB |
| Total Run Time: | 1:01 minutes |

### 3.2.5 Restrictions Imposed in Processing Order

Relative to the target PGE CER3.1P1 data date, this PGE depends on the first day of the next month. For the input requirements (see Section 3.3.1).

## 3.3 Processor Dependencies (Previous PGEs, Ingest Data,..)

***Note: Include all required inputs such as .met files, header files, etc.***

### 3.3.1 Input Dataset Name (#1): preES-8

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

   **$CERESHOME/instrument/data/out_comp/**
   **CER_PRES8_$SS1_$PS1_$CC1_2.yyyymmdd**

   1. Mandatory/Optional: **This file is mandatory.**
   2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
   3. Waiting Period: **None, process when all input data are available.**

b. Source of Information (Source is PGE name or Ingest Source):

   **Source PGE: CER1.2P1**

c. Alternate Data Set, if one exists (maximum waiting period):

**Reprocessing ERBE data using the ERBE S-8,** Section 3.3.2.

d. File Disposition after successful execution: **Do not remove until monthly processing (Subsystem 3.0) is complete.**

e. Typical file size (MB): **283**

### 3.3.2 Alternate Dataset Name (#1): S-8

**Reprocess ERBE data from November 5, 1984 through February 28, 1990**

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/instrument/data/out_comp/s8_yymmdd_sc**
where, sc is the satellite number: "1" for NOAA9, "2" for ERBS, or "3" for NOAA10.

1. Mandatory/Optional: **This file is mandatory.**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
3. Waiting Period: **None, process when all input data are available (see** Section 3.2.5**).**

b. Source of Information (Source is PGE name or Ingest Source):

**Ingest Source: LaTIS.**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Do not remove until monthly processing (Subsystem 3.0) is complete.**

e. Typical file size (MB): **37**

### 3.3.3 Input Dataset Name (#2): SNOW

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/erbelike/data/ancillary/dynamic/**
**CER_SNOW_$SS2_1_$PS2_1_$CC2_1.yyyymm**

1. Mandatory/Optional: **This file is mandatory.**
2. Time Related Dependency: **The data date must match the PGE CER3.1P1 runtime parameters: yyyy, mm (See *CERES ERBE-like Averaging to Monthly TOA Fluxes Subsystem 3.0 Release 3 Operator's Manual*, Table 1-4)**
3. Waiting Period: **One month, process when all input data are available.**

b. Source of Information (Source is PGE name or Ingest Source):

**Source PGE: CER2.1P1**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Do not remove.**

e. Typical file size (MB): **.03**

### 3.3.4 Input Dataset Name (#3): Spectral Response and Correction Coefficients

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/erbelike/data/ancillary/dynamic/**
**CER_SCCD_$SS2_$PS2_4_$CC2_4.yyyymmdd**
**CER_SCCN_$SS2_$PS2_4_$CC2_4.yyyymmdd**

1. Mandatory/Optional: **This file is mandatory.**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
3. Waiting Period: **One month, process when all input data are available.**

b. Source of Information (Source is PGE name or Ingest Source):

**Source PGE: CER2.4P1**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Do not remove.**

e. Typical file size (MB): **.55, and .02**

## 3.4 Operating Procedures (Procedure for each part of the processor's elements)

The production script, **CER2.3P1**, references a Process Control File (PCF) which contains the file names and paths for the PGE. This PCF is created by first sourcing the ERBE-like-specific environment script, **ENVerbelike-env.csh**, then executing an ASCII file and PCF generator, **gen_pcf.CER2.3**.

### 3.4.1 How to Generate the ASCII File and PCF

The ASCII file and PCF generator requires five command-line arguments: data date (yyyymmdd), the snow file parameter (either Actual (A) or Composite (C)), ADM structure (either Original (F) or New (N)), Spectral Correction Algorithm (either Original (F), Slope Intercept Method (N), or Slope Intercept Method using the daily Spectral Response Function and Correction Coefficient Files generated by PGE CER2.4P1 (D)), and SW offsets (either day/night (D), thermal SW offsets (T), or no offsets (Z)) (see Table 3-3).

At the command-line (>) type:

> **cd $CERESHOME/erbelike/data/scr**
> **source $CERESHOME/erbelike/bin/ENVerbelike-env.csh**
> **$CERESHOME/erbelike/bin/gen_pcf.CER2.3P1 yyyymmdd snow adm spcor swoff**

The following files are generated and located in **$CERESHOME/erbelike/rcf/pcf/**:

**CER2.3P1_PCFin_$SS2_$PS2_$CC2.yyyymmdd**
**CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd**

### 3.4.2 How to Execute the Main-Processor

Clear the output directories of files previously generated from this PGE by executing script, **clr_dir.PGE2.3**, with the runtime parameter data date. Before running the program, make sure the executables (pre_es8.exe, inv.exe, ddbint.exe, and ddbupd.exe) are in the $CERESHOME/ erbelike/bin directory. Execute the production script by typing the script name, **CER2.2P1**, followed by a string which designates the instance of the data. The string should be formatted, "Sampling Strategy"_"Production Strategy"_"Configuration Code"."DataDate". The date parameter is formatted, yyyymmdd, where yyyy is the data year, mm is the data month, and dd is the data day (see Table 3-3).

At the command-line (>) type:

> **cd $CERESHOME/erbelike/data/scr**
> **$CERESHOME/erbelike/bin/clr_dir.PGE2.3 yyyymmdd**
> **$CERESHOME/erbelike/bin/CER2.3P1 $SS2_$PS2_$CC2.yyyymmdd**

### 3.4.3 Special Case Considerations

N/A, at this time. Special case considerations will be handled on a case-by-case basis, where instructions will accompany each special request.

### 3.4.4 Special Reprocessing Instructions

1. All output files are opened with Status = NEW in the CER2.3P1 software. These files must be removed before rerunning these procedures. A script, which removes PGE created files, **clr_dir.PGE2.3**, is located in directory $CERESHOME/erbelike/bin. Using yyyymmdd as a command line argument:

   > **$CERESHOME/erbelike/bin/clr_dir.PGE2.3 yyyymmdd**

2. See reprocessing requirements in the "CERES DMT to DAAC Processing Request" available on the Web at: http://asd-www.larc.nasa.gov/ceres/dmt2daac/.

## 3.5 Execution Evaluation

### 3.5.1 Exit Codes

The processor CER2.3P1 terminates using the CERES-defined EXIT CODES for the Langley TRMM Information System (LaTIS) as seen in Table 3-4. Other Exit Codes may appear from the program, which may be the result of a system, compiler, or Toolkit related error. In these cases, contact the responsible person for assistance (see Table 1-1).

Table 3-4. Exit Codes for CER2.3P1

| Exit Code | Definition | Action |
|---|---|---|
| 0 | Normal Exit | Proceed normally |
| 198 | Fatal | "PCF: CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd DoesNOT exist" Inform the primary contact in Table 1-1. |
| 199 | Fatal | "CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in pres8 conversion" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 200 | Fatal | "CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in inversion" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 201 | Fatal | "CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in ddbint" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 202 | Fatal | "CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in ddbupd" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |

### 3.5.2 Screen Messages (Use Table format for large number of messages.)

Table 3-5. Screen Messages for execution of CER2.3P1 (1 of 2)

| Message | Definition/Action |
|---|---|
| Cannot access <filename>: No such file or directory | This message occurs when the script tries to remove an old output file that does not exist. This does not signify a problem. |
| CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd SUCCESSFULLY terminated<br>Exit Status = 0 | This message is written to the screen to signify that PGE CER2.3P1 has successfully completed. Proceed normally. |

Table 3-5. Screen Messages for execution of CER2.3P1 (2 of 2)

| Message | Definition/Action |
|---|---|
| PCF: CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd DoesNOT exist<br>Exit Status = 198 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in pres8<br>Exit Status = 199 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in inversion<br>Exit Status = 200 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in ddbint<br>Exit Status = 201 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.3P1 CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in ddbupd<br>Exit Status = 202 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |

### 3.5.3 Log and Status Files Results (Include ALL Log Files)

The Log files contain all error and/or status messages produced by the PGE. The files are located in the directory: **$CERESHOME/erbelike/data/runlogs**.

#### 3.5.3.1 Report Log File: CER2.3P1_LogReport_$SS2_$PS2_$CC2.yyyymmdd

The Report Log File contains the PGE CER2.3P1 generated messages. These messages may be strictly informative (Error Type = Status or Warning) or may indicate a fatal condition that results in premature PGE termination (Error Type = Fatal). A comprehensive list of these messages, that can be generated during the execution of the PGE, is contained in Appendix B.

#### 3.5.3.2 Status Log File: CER2.3P1_LogStatus_$SS2_$PS2_$CC2.yyyymmdd

The Status Log File contains all messages created by the Toolkit. If an abnormal exit is encountered by the PGE, this file should be examined for '_F_', fatal message type. The responsible person should be advised (see Table 1-1).

#### 3.5.3.3 User Log File: CER2.3P1_LogUser_$SS2_$PS2_$CC2.yyyymmdd

The User Log File is not used at this time, but exists to satisfy the Toolkit requirements. Typically the '_U_' and '_N_' (User information and Notice) will be written to the User Log File and the Status Log File.

### 3.5.4 Solutions to Possible Problems

If problems occur, consult the primary contact in Table 1-1.

### 3.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing)

a. Subsystem Termination

Please refer to Appendix B for a descriptive list of all errors and the result of those errors.

b. Target PGE Termination

Please refer to Appendix B for a descriptive list of all errors and the result of those errors. If .met files have not been created, the target PGE should not run. Target PGEs should not be processed in instances of PGE failure.

## 3.6 Expected Output Dataset(s)

(Note: Include all expected Web files.)
The expected output datasets are listed below for each instance of the PGE. This PGE is expected to run once a month.

Table 3-6. Expected Output File Listing for CER2.3P1 (1 of 2)

| File Name[a]/Directory | m/o[b] | File Size (MB) | Freq/ PGE | Target PGE | Destination[c] |
|---|---|---|---|---|---|
| CER2.3P1_PCF_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.030 | 1/month | N/A | Archive rm |
| CER2.3P1_PCFin_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.002 | 1/month | N/A | Archive rm |
| CER2.3P1_LogReport_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.010 | 1/month | N/A | Archive rm |
| CER2.3P1_LogStatus_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.006 | 1/month | N/A | Archive rm |
| CER2.3P1_LogUser_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.001 | 1/month | N/A | Archive rm |
| CER_CQCIX_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | m | 0.11 | 1/month | N/A | Archive rm |
| CER_EID6X_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | o | 11.85 | 1/month | N/A | Archive rm |
| CER_CXDR_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/ddb) | o | 1.10 | 1/month | CER3.1P1 | Archive |

Table 3-6. Expected Output File Listing for CER2.3P1 (2 of 2)

| File Name[a]/Directory | m/o[b] | File Size (MB) | Freq/ PGE | Target PGE | Destination[c] |
|---|---|---|---|---|---|
| CER_CQCD_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/ddb) | o | 0.05 | 1/month | N/A | Archive rm |
| CER_CMSGX_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/runlogs) | m | 0.015 | 1/month | N/A | Archive rm |

a. See Section 3.2 for information on variable data values.
If "(.met)" is written next to an expected output filename, then the metatdata file with the identical filename and .met extension must exist.
Note: yyyy - 4-digit year (See Runtime Parameters Table 3-3)
mm - 2-digit month {valid values: 01 .. 12} (See Runtime Parameters Table 3-3)
dd - 2-digit day {valid values: 01 .. 31} (See Runtime Parameters Table 3-3)
b. Note: m - mandatory output
o - optional output
c. Note: /QA - File is to be written to the DAAC designated /QA directory
rm - remove

## 3.7 Expected Temporary Files/Directories.

Table 3-7. Temporary Files Listing for CER2.3P1

| Directory | File Name |
|---|---|
| $CERESHOME/erbelike/data/runlogs | ShmMem |

# 4.0 PGEName: CER2.3P2

**CERES ERBE-like Monthly Inversion for the Last Day of the Previous Month.**
Note: This PGE is run prior to PGE CER3.1P1 if there is input data from the last day of the previous month.

## 4.1 PGE Details

### 4.1.1 Responsible Persons

See Table 1-1, Subsystem Software Analysts Contacts.

### 4.1.2 E-mail Distribution List

E-mail distribution list can be obtained from the primary contact listed in Table 1-1.

### 4.1.3 Parent PGE(s)

A parent PGE generates data for input to the current PGE, CER2.3P2.

Table 4-1. Parent PGEs for CER2.3P2

| PGEName | Description |
|---|---|
| CER1.2P1 | CERES BDS to Pre-ES8 conversion post-processor. |
| CER2.1P1 | CERES ERBE-like Monthly Geo-Scene and Snow Map, and Longwave Flux and Albedo Thresholds. |
| CER2.4P1 | CERES ERBE-like Spectral Response Functions and Correction Coefficients. |

### 4.1.4 Target PGE(s)

A target PGE requires input data generated from the current PGE, CER2.3P2.

Table 4-2. Target PGEs after CER2.3P2

| PGEName | Description |
|---|---|
| CER3.1P1 | CERES ERBE-like Monthly TOA Flux Averaging Main-Processor for FAPS+RAPS data for a Single Instrument. |

## 4.2 Operating Environment

### 4.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.)

The runtime parameters of PGE CER2.3P2 are relative to a target processing month in that for a given month, PGE CER2.3P2 supplies overlap data from the last day of the month previous to the target processing month. Therefore, where the descriptions "CERDataDateYear" and "CERDataDateMonth" are used, these descriptions will refer to the month and year of data for the target processing month.

Table 4-3. Runtime Parameters for CER2.3P2

| Parameter[a] | Description | Valid Values |
|---|---|---|
| yyyy | 4-digit Year corresponding to the month before the CERData-DateMonth | >= 1984 |
| mm | 2-digit Month before CERDataDateMonth | 01 .. 12 |
| dd | Last day (2-digit) of the month before CERDataDateMonth | 28 .. 31 |
| snow | Type of input snow file "Actual" or "Composite" | "A" or "C" |
| adm | Original or New Angular Directional Model structure | "F" or "N" |
| spcor | Original, Slope Intercept Spectral Correction Algorithm, or Instrument Team's modified input for the Slope Intercept Spectral Correction Algorithm. | "F", "N", "D" or "M" |
| swoff | Type of SW Offset "Day/Night", "Thermal" or "No offsets" | "D", "T", or "Z" |

a. All character strings.

### 4.2.2 Environment Script Requirements

Refer to the CERES internal paper (Reference 3) for a detailed description of the CERES environment parameters. For the current values of the Sampling Strategy and Production Strategy variables listed below, see "CERES DMT to DAAC Processing Request." (URL: http://asd-www.larc.nasa.gov/ceres/dmt2daac/)

One environment script is required. It is named '**ENVerbelike-env.csh**' and contains the following parameters:

SS1 - Sampling Strategy for CER1.2P1, see Production Request (Reference 4)
SS2_1 - Sampling Strategy for CER2.1P1, see Production Request (Reference 4)
SS2 - Sampling Strategy for CER2.2P1, see Production Request (Reference 4)
PS1 - Production Strategy for CER1.2P1, see Production Request (Reference 4)
PS2_1 - Production Strategy for CER2.1P1, see Production Request (Reference 4)
PS2_4 - Production Strategy for CER2.4P1, see Production Request (Reference 4)
PS2 - Production Strategy for CER2.2P1, see Production Request (Reference 4)

CC1_2 - Configuration Code for CER1.2P1, see CM Database
CC2_1 - Configuration Code for CER2.1P1, see CM Database
CC2_4 - Configuration Code for CER2.4P1, see CM Database
CC2 - Configuration Code for CER2.2P1, see CM Database
SAT - Satellite, see Production Request (Reference 4)
IMAG - Imager, see Production Request (Reference 4)
INST - Instrument, see Production Request (Reference 4)

#### 4.2.3 Execution Frequency (daily,hourly,..)

**monthly (1/month)** - This PGE, along with PGE CER2.3P1, is to be processed once per month, immediately before PGE CER3.1P1.

#### 4.2.4 Memory/Disk Space/Time Requirements

| | |
|---|---|
| Memory: | 5.3 MB |
| Disk Space: | 13 MB |
| Total Run Time: | 1:05 minutes |

#### 4.2.5 Restrictions Imposed in Processing Order

Relative to the target PGE CER3.1P1 data date, this PGE depends on the last day of the previous month. For the input requirements (see Section 4.3).

### 4.3 Processor Dependencies (Previous PGEs, Ingest Data,..)

***Note: Include all required inputs such as .met files, header files, etc.***

#### 4.3.1 Input Dataset Name (#1): preES-8

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

   **$CERESHOME/instrument/data/out_comp/**
   **CER_PRES8_$SS1_$PS1_$CC1_2.yyyymmdd**

   1. Mandatory/Optional: **This file is mandatory.**
   2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
   3. Waiting Period: **None, process when all input data are available.**

b. Source of Information (Source is PGE name or Ingest Source):

   **Source PGE: CER1.2P1**

c. Alternate Data Set, if one exists (maximum waiting period):

**Reprocessing ERBE data using the ERBE S-8,** Section 4.3.2**.**

d. File Disposition after successful execution: **Do not remove until monthly processing (Subsystem 3.0) is complete. The file for "<u>the last day of the month</u>" cannot be removed until the monthly processing of the following month is complete.**

e. Typical file size (MB): **283**

### 4.3.2 Alternate Dataset Name (#1): S-8

**Reprocess ERBE data from November 5, 1984 through February 28, 1990**

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/instrument/data/out_comp/s8_yymmdd_sc**
where, sc is the satellite number: "1" for NOAA9, "2" for ERBS, or "3" for NOAA10.

1. Mandatory/Optional: **This file is mandatory.**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
3. Waiting Period: **None, process when all input data are available (see** Section 4.2.5**).**

b. Source of Information (Source is PGE name or Ingest Source):

**Ingest Source: LaTIS.**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Do not remove until monthly processing (Subsystem 3.0) is complete.**

e. Typical file size (MB): **37**

### 4.3.3 Input Dataset Name (#2): SNOW

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/erbelike/data/ancillary/dynamic/**
**CER_SNOW_$SS2_1_$PS2_1_$CC2_1.yyyymm**

1. Mandatory/Optional: **This file is mandatory.**
2. Time Related Dependency: **The data date must match the PGE CER3.1P1 runtime parameters: yyyy, mm (See *CERES ERBE-like Averaging to Monthly TOA Fluxes Subsystem 3.0 Release 3 Operator's Manual*, Table 1-4)**
3. Waiting Period: **One month, process when all input data are available.**

b. Source of Information (Source is PGE name or Ingest Source):

**Source PGE: CER2.1P1**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Do not remove.**

e. Typical file size (MB): **.03**

#### 4.3.4 Input Dataset Name (#3): Spectral Response and Correction Coefficients

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/erbelike/data/ancillary/dynamic/**
**CER_SCCD_$SS2_$PS2_4_$CC2_4.yyyymmdd**
**CER_SCCN_$SS2_$PS2_4_$CC2_4.yyyymmdd**

1. Mandatory/Optional: **This file is mandatory.**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
3. Waiting Period: **One month, process when all input data are available.**

b. Source of Information (Source is PGE name or Ingest Source):

**Source PGE: CER2.4P1**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Do not remove.**

e. Typical file size (MB): **.55, and .02**

## 4.4 Operating Procedures (Procedure for each part of the processor's elements)

The production script, **CER2.3P2**, references a Process Control File (PCF) which contains the file names and paths for the PGE. This PCF is created by first sourcing the ERBE-like-specific environment script, **ENVerbelike-env.csh**, then executing an ASCII file and PCF generator, **gen_pcf.CER2.3**.

### 4.4.1 How to Generate the ASCII File and PCF

The ASCII file and PCF generator requires five command-line arguments: data date (yyyymmdd), the snow file parameter (either Actual (A) or Composite (C)), ADM structure (either Original (F) or New (N)), Spectral Correction Algorithm (either Original (F), Slope Intercept Method (N), or Slope Intercept Method using the daily Spectral Response Function and Correction Coefficient Files generated by PGE CER2.4P1 (D)), and SW offsets (either day/night (D), thermal SW offsets (T), or no offsets (Z)) (see Table 4-3).

At the command-line (>) type:

> **cd $CERESHOME/erbelike/data/scr**
> **source $CERESHOME/erbelike/bin/ENVerbelike-env.csh**
> **$CERESHOME/erbelike/bin/gen_pcf.CER2.3P2 yyyymmdd snow adm spcor swoff**

The following files are generated and located in **$CERESHOME/erbelike/rcf/pcf/**:

**CER2.3P2_PCFin_$SS2_$PS2_$CC2.yyyymmdd**
**CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd**

### 4.4.2 How to Execute the Main-Processor

Clear the output directories of files previously generated from this PGE by executing script, **clr_dir.PGE2.3**, with the runtime parameter data date. Before running the program, make sure the executables (pre_es8.exe, inv.exe, ddbint.exe, and ddbupd.exe) are in the $CERESHOME/erbelike/bin directory. Execute the production script by typing the script name, **CER2.3P2**, followed by a string which designates the instance of the data. The string should be formatted, "Sampling Strategy"_"Production Strategy"_"Configuration Code"."DataDate". The date parameter is formatted, yyyymmdd, where yyyy is the data year, mm is the data month, and dd is the data day (see Table 4-3).

At the command-line (>) type:

> **cd $CERESHOME/erbelike/data/scr**
> **$CERESHOME/erbelike/bin/clr_dir.PGE2.3 yyyymmdd**
> **$CERESHOME/erbelike/bin/CER2.3P2 $SS2_$PS2_$CC2.yyyymmdd**

### 4.4.3 Special Case Considerations

N/A, at this time. Special case considerations will be handled on a case-by-case basis, where instructions will accompany each special request.

### 4.4.4 Special Reprocessing Instructions

1. All output files are opened with Status = NEW in the CER2.3P2 software. These files must be removed before rerunning these procedures. A script, which removes PGE created files, **clr_dir.PGE2.3**, is located in directory $CERESHOME/erbelike/bin. Using yyyymmdd as a command line argument:

   > **$CERESHOME/erbelike/bin/clr_dir.PGE2.3 yyyymmdd**

2. See reprocessing requirements in the "CERES DMT to DAAC Processing Request" available on the Web at: http://asd-www.larc.nasa.gov/ceres/dmt2daac/.

## 4.5 Execution Evaluation

### 4.5.1 Exit Codes

The processor CER2.3P2 terminates using the CERES-defined EXIT CODES for the Langley TRMM Information System (LaTIS) as seen in Table 4-4. Other Exit Codes may appear from the program, which may be the result of a system, compiler, or Toolkit related error. In these cases, contact the responsible person for assistance (see Table 1-1).

Table 4-4. Exit Codes for CER2.3P2

| Exit Code | Definition | Action |
|---|---|---|
| 0 | Normal Exit | Proceed normally |
| 198 | Fatal | "PCF: CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd DoesNOT exist" Inform the primary contact in Table 1-1 |
| 199 | Fatal | "CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in pres8 conversion" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 200 | Fatal | "CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in inversion" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 201 | Fatal | "CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in ddbint" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |
| 202 | Fatal | "CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in ddbupd" Check the Log files, inform the primary contact in Table 1-1, and take the appropriate action (see Appendix B). |

### 4.5.2 Screen Messages (Use Table format for large number of messages.)

Table 4-5. Screen Messages for execution of CER2.3P2 (1 of 2)

| Message | Definition/Action |
|---|---|
| Cannot access <filename>: No such file or directory | This message occurs when the script tries to remove an old output file that does not exist. This does not signify a problem. |
| CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd SUCCESSFULLY terminated<br>Exit Status = 0 | This message is written to the screen to signify that PGE CER2.3P2 has successfully completed. Proceed normally. |
| PCF: CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd DoesNOT exist<br>Exit Status = 198 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |

Table 4-5. Screen Messages for execution of CER2.3P2 (2 of 2)

| Message | Definition/Action |
|---|---|
| CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in pres8 conversion Exit Status = 199 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in inversion Exit Status = 200 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in ddbint Exit Status = 201 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.3P2 CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd UNSUCCESSFULLY terminated in ddbupd Exit Status = 202 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |

### 4.5.3 Log and Status Files Results (Include ALL Log Files)

The Log files contain all error and/or status messages produced by the PGE. The files are located in the directory: **$CERESHOME/erbelike/data/runlogs**.

#### 4.5.3.1 Report Log File: CER2.3P2_LogReport_$SS2_$PS2_$CC2.yyyymmdd

The Report Log File contains the PGE CER2.3P2 generated messages. These messages may be strictly informative (Error Type = Status or Warning) or may indicate a fatal condition that results in premature PGE termination (Error Type = Fatal). A comprehensive list of these messages, that can be generated during the execution of the PGE, is contained in Appendix B.

#### 4.5.3.2 Status Log File: CER2.3P2_LogStatus_$SS2_$PS2_$CC2.yyyymmdd

The Status Log File contains all messages created by the Toolkit. If an abnormal exit is encountered by the PGE, this file should be examined for '_F_', fatal message type. The responsible person should be advised (see Table 1-1).

#### 4.5.3.3 User Log File: CER2.3P2_LogUser_$SS2_$PS2_$CC2.yyyymmdd

The User Log File is not used at this time, but exists to satisfy the Toolkit requirements. Typically the '_U_' and '_N_' (User information and Notice) will be written to the User Log File and the Status Log File.

### 4.5.4 Solutions to Possible Problems

If problems occur, consult the primary contact in Table 1-1.

### 4.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing)

a. Subsystem Termination

Please refer to Appendix B for a descriptive list of all errors and the result of those errors.

b. Target PGE Termination

Please refer to Appendix B for a descriptive list of all errors and the result of those errors. If .met files have not been created, the target PGE should not run. Target PGEs should not be processed in instances of PGE failure.

## 4.6 Expected Output Dataset(s)

(Note: Include all expected Web files.)
The expected output datasets are listed below for each instance of the PGE. This PGE is expected to run once a month.

Table 4-6. Expected Output File Listing for CER2.3P2 (1 of 2)

| File Name[a]/Directory | m/o[b] | File Size (MB) | Freq/ PGE | Target PGE | Destination[c] |
|---|---|---|---|---|---|
| CER2.3P2_PCF_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.030 | 1/month | N/A | Archive rm |
| CER2.3P2_PCFin_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.002 | 1/month | N/A | Archive rm |
| CER2.3P2_LogReport_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.010 | 1/month | N/A | Archive rm |
| CER2.3P2_LogStatus_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.006 | 1/month | N/A | Archive rm |
| CER2.3P2_LogUser_$SS2_$PS2_$CC2.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.001 | 1/month | N/A | Archive rm |
| CER_CQCIX_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | m | 0.11 | 1/month | N/A | Archive rm |
| CER_EID6X_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/inv) | o | 11.85 | 1/month | N/A | Archive rm |
| CER_CXDR_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/ddb) | o | 1.10 | 1/month | CER3.1P1 | Archive |

Table 4-6. Expected Output File Listing for CER2.3P2 (2 of 2)

| File Name[a]/Directory | m/o[b] | File Size (MB) | Freq/ PGE | Target PGE | Destination[c] |
|---|---|---|---|---|---|
| CER_CQCD_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/out_comp/data/ddb) | o | 0.05 | 1/month | N/A | Archive rm |
| CER_CMSGX_$SS2_$PS2_$CC2.yyyymmdd (.met) @($CERESHOME/erbelike/data/runlogs) | m | 0.015 | 1/month | N/A | Archive rm |

a. See Section 4.2 for information on variable data values.
If "(.met)" is written next to an expected output filename, then the metatdata file with the identical filename and .met extension must exist.
Note: yyyy - 4-digit year (See Runtime Parameters Table 4-3)
mm - 2-digit month {valid values: 01 .. 12} (See Runtime Parameters Table 4-3)
dd - 2-digit day {valid values: 01 .. 31} (See Runtime Parameters Table 4-3)
b. Note: m - mandatory output
o - optional output
c. Note: /QA - File is to be written to the DAAC designated /QA directory
rm - remove

## 4.7 Expected Temporary Files/Directories

Table 4-7. Temporary Files Listing for CER2.3P2

| Directory | File Name |
|---|---|
| $CERESHOME/erbelike/data/runlogs | ShmMem |

# 5.0 PGEName: CER2.4P1

**CERES ERBE-like Spectral Response Functions and Correction Coefficients**

## 5.1 PGE Details

### 5.1.1 Responsible Persons

See Table 1-1, Subsystem Software Analysts Contacts.

### 5.1.2 E-mail Distribution List

E-mail distribution list can be obtained from the primary contact listed in Table 1-1.

### 5.1.3 Parent PGE(s)

A parent PGE generates data for input to the current PGE, CER2.4P1. PGE CER2.4P1 is only dependent on outside data sources and has no parent PGE(s).

### 5.1.4 Target PGE(s)

A target PGE requires input data generated from the current PGE, CER2.4P1.

Table 5-1. Target PGEs after CER2.4P1

| PGEName | Description |
|---|---|
| CER2.2P1 | CERES ERBE-like Daily Inversion to Instantaneous TOA Fluxes Main-Processor for FAPS+RAPS data for a Single Instrument. |
| CER2.3P1 | CERES ERBE-like Monthly Inversion to Instantaneous TOA Fluxes Overlap-Processor for FAPS+RAPS data for a Single Instrument for the First Day of the Next Month. |
| CER2.3P2 | CERES ERBE-like Monthly Inversion to Instantaneous TOA Fluxes Overlap-Processor for FAPS+RAPS data for a Single Instrument for the Last Day of the Previous Month. |
| CER4.5-6.1P2 | CERES Inversion to Instantaneous TOA Fluxes and Empirical Estimates of Surface Radiation Budget Subsystems 4.5 and 4.6 Main Processor and HDF Postprocessor |

## 5.2 Operating Environment

### 5.2.1 Runtime Parameters (List all dynamic parameters needed at runtime.)

Table 5-2. Runtime Parameters for CER2.4P1

| Parameter[a] | Description | Valid Values |
|---|---|---|
| yyyy | 4-digit CERDataDateYear | >= 1984 |
| mm | 2-digit CERDataDateMonth | 01 .. 12 |
| dd | 2-digit CERDataDateDay | 01 .. 31 |
| xxx | 1 to 3-digit instrument channel designator for any combination of Shortwave, Total, or Window channels | 1,2,3, 12,13,23, or 123 |

a. All character strings.

### 5.2.2 Environment Script Requirements

Refer to the CERES internal paper (Reference 3) for a detailed description of the CERES environment parameters. For the current values of the Sampling Strategy and Production Strategy variables listed below, see "CERES DMT to DAAC Processing Requests." (URL: http://asd-www.larc.nasa.gov/ceres/dmt2daac/)

One environment script is required. It is named '**ENVerbelike-env.csh**' and contains the following parameters:

SS2 - Sampling Strategy for CER2.2P1, see Production Request (Reference 4)
PS2_4 - Production Strategy for CER2.4P1, see Production Request (Reference 4)
CC2_4 - Configuration Code for CER2.4P1, see CM Database
SAT - Satellite, see Production Request (Reference 4)
IMAG - Image, see Production Request (Reference 4)
INST - Instrument, see Production Request (Reference 4)

### 5.2.3 Execution Frequency (daily,hourly,..)

### 5.2.4 Memory/Disk Space/Time Requirements

Memory: 7.5 MB
Disk Space: 4480 MB
Total Run Time: 32:54 minutes

### 5.2.5 Restrictions Imposed in Processing Order

PGE CER2.4P1 requires the time dependent spectral response function file that matches the runtime parameter data date or two time dependent spectral response function files for each instrument channel being processed corresponding to data dates needed for interpolation or extrapolation to the runtime parameter data date. If the required number of input files are not available, contact the Subsystem software analysts from Table 1-1.

## 5.3 Processor Dependencies (Previous PGEs, Ingest Data,..)

***Note: Include all required inputs such as .met files, header files, etc.***

### 5.3.1 Input Dataset Name (#1): Time dependent spectral response functions

a. Directory Location/Inputs Expected (Including .met files, header files, etc.):

**$CERESHOME/erbelike/data/input/ :**
**SRF_$SS2_SW.datadate.proddate**
**SRF_$SS2_TOT.datadate.proddate**
**SRF_$SS2_WN.datadate.proddate**

where, proddate is the date the files were produced. The proddate is formatted, yyyymmdd, where yyyy is the production year, mm is the production month, and dd is the production day (see Table 5-2).
The data date, datadate, is formatted yyyymmdd, where yyyy is the data year, mm is the data month, and dd is the data day (see Table 5-2).

**If a time dependent spectral response function file date exists for the runtime parameter data date, then only that time dependent spectral response function file is needed for input. If a time dependent spectral response function file date does not exist for the runtime parameter data date, then two input files are need for interpolation or extrapolation.**

1. Mandatory/Optional: **These files are optional. The CERES instrument team will determine the use of these files.**
2. Time Related Dependency: **The data date must match the runtime parameters: yyyy, mm, dd.**
3. Waiting Period: **Run PGE when data for the data day are available.**

b. Source of Information (Source PGE name or Ingest Source):

**Ingest Source - CERES Instrument Team.**

c. Alternate Data Set, if one exists (maximum waiting period): **None.**

d. File Disposition after successful execution: **Do not remove until daily processing (Subsystem 2.0) is complete.**

e. Typical file size (KB): **8.5, 17.9, & 21.8**

## 5.4 Operating Procedures (Procedure for each part of the processor's elements)

The production script, **CER2.4P1**, references a Process Control File (PCF) which contains the file names and paths for the PGE. This PCF is created by executing an ASCII file and PCF generator, **gen_pcf.CER2.4P1**.

### 5.4.1 How to Generate the ASCII File and PCF

The ASCII file and PCF generator requires two command-line arguments: data date (yyyymmdd), the instrument channel designator (either 1, 2, 3, 12, 13, 23, or 123) (see Table 5-2).

At the command-line (>) type:

**> cd $CERESHOME/erbelike/data/scr**
**> $CERESHOME/erbelike/bin/gen_pcf.CER2.4P1 yyyymmdd xxx**

The following files are generated and located in **$CERESHOME/erbelike/rcf/pcf/**:

**CER2.4P1_PCFin_$SS2_$PS2_4_$CC2_4.yyyymmdd**
**CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd**

### 5.4.2 How to Execute the Main-Processor

Clear the output directories of files previously generated from this PGE by executing script, **clr_dir.PGE2.4**, with the runtime parameter data date. Before running the program, make sure the executables (scc_calbkn.exe, scc_interp_resp.exe, scc_meta.exe, scc_regr.exe, scc_regr_lw.exe, scc_spcoef.exe, scc_spcoef_lnd.exe, scc_spcoef_night.exe, scc_spcoef_night_lnd.exe, and scc_stitch.exe) are in the $CERESHOME/erbelike/bin directory. Execute the production script by typing the script name, **CER2.4P1**, followed by a string which designates the instance of the data. The string should be formatted, "Sampling Strategy"_"Production Strategy"_"Configuration Code"."DataDate". The date parameter is formatted, yyyymmdd, where yyyy is the data year, mm is the data month, and dd is the data day (see Table 5-2).

At the command-line (>) type:

**> cd $CERESHOME/erbelike/data/scr**
**> $CERESHOME/erbelike/bin/clr_dir.CER2.4P1 yyyymmdd**
**> $CERESHOME/erbelike/bin/CER2.4P1 $SS2_$PS2_4_$CC2_4.yyyymmdd**

### 5.4.3 Special Case Considerations

N/A, at this time. Special case considerations will be handled on a case-by-case basis, where instructions will accompany each special request.

### 5.4.4 Special Reprocessing Instructions

1. All output files are opened with Status = NEW in the CER2.4P1 software. These files must be removed before rerunning these procedures. A script, which removes PGE created files, **clr_dir.CER2.4P1**, is located in directory $CERESHOME/erbelike/bin. Using data date as a command line argument:

   > **$CERESHOME/erbelike/bin/clr_dir.CER2.4P1 yyyymmdd**

2. See reprocessing requirements in "CERES DMT to DAAC Processing Requests" available on the Web at: http://asd-www.larc.nasa.gov/ceres/docs.html.

## 5.5 Execution Evaluation

### 5.5.1 Exit Codes

The processor CER2.4P1 terminates using the CERES-defined EXIT CODES for the Langley TRMM Information System (LaTIS) as seen in Table 5-3. Other exit codes may appear from the program, which may be the result of a system, compiler, or Toolkit related error. In these cases, contact the responsible person for assistance (see Table 1-1).

Table 5-3. Exit Codes for CER2.4P1 (1 of 2)

| Exit Code | Definition | Action |
|---|---|---|
| 0 | Normal Exit | Proceed normally |
| 198 | Fatal | "PCF: CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymm DoesNOT exist" Inform the primary contact in Table 1-1 |
| 210 | Fatal | Check the "ChannelCode" in the PC file, inform the primary contact from Table 1-1, and take the appropriate action (see Appendix B). |
| 211 | Fatal | Check the Log files, inform the primary contact from Table 1-1, and take the appropriate action (see Appendix B). |
| 212 | Fatal | Check the Log files, inform the primary contact from Table 1-1, and take the appropriate action (see Appendix B). |
| 213 | Fatal | Check the Log files, inform the primary contact from Table 1-1, and take the appropriate action (see Appendix B). |
| 214 | Fatal | Check the Log files, inform the primary contact from Table 1-1, and take the appropriate action (see Appendix B). |

Table 5-3. Exit Codes for CER2.4P1 (2 of 2)

| Exit Code | Definition | Action |
|---|---|---|
| 215 | Fatal | Check the Log files, inform the primary contact from Table 1-1, and take the appropriate action (see Appendix B). |

### 5.5.2 Screen Messages (Use Table format for large number of messages)

Table 5-4. Screen Messages for execution of CER2.4P1 (1 of 2)

| Message | Definition/Action |
|---|---|
| Cannot access <filename>: No such file or directory | This message occurs when the script tries to remove an old output file that does not exist. This does not signify a problem. |
| CER2.4P1<br>CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd<br>SUCCESSFULLY terminated<br>Exit Status = 0 | This message is written to the screen to signify that PGE CER2.4P1 has successfully completed. Proceed normally. |
| PCF: CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd<br>DoesNOT exist<br>Exit Status = 198 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.4P1<br>CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd<br>UNSUCCESSFULLY terminated<br>Invalid Channel_Code<br>Exit Status = 210 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B) |
| CER2.4P1<br>CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd<br>UNSUCCESSFULLY terminated in scc_interp_resp<br>Exit Status = 211 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.4P1<br>CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd<br>UNSUCCESSFULLY terminated in scc_gen.csh<br>Exit Status = 212 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.4P1<br>CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd<br>UNSUCCESSFULLY terminated in scc_meta<br>Exit Status = 213 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |
| CER2.4P1<br>CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd<br>UNSUCCESSFULLY terminated in scc_checker<br>Exit Status = 214 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |

Table 5-4. Screen Messages for execution of CER2.4P1 (2 of 2)

| Message | Definition/Action |
|---|---|
| CER2.4P1<br>CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd<br>UNSUCCESSFULLY terminated in trendplot.csh<br>Exit Status = 215 | This message is written to the screen signifying a fatal error has occurred. Refer to the Log files for more detailed information (see Appendix B). |

### 5.5.3 Log and Status Files Results (Include ALL Log Files)

The Log files contain all error and/or status messages produced by the PGE. The files are located in the directory: **$CERESHOME/erbelike/data/runlogs**.

#### 5.5.3.1 Report Log File: CER2.4P1_LogReport_$SS2_$PS2_4_$CC2_4.yyyymmdd

The Report Log File contains the PGE CER2.4P1 generated messages. These messages may be strictly informative (Error Type = Status or Warning) or may indicate a fatal condition that results

in premature PGE termination (Error Type = Fatal). A comprehensive list of these messages, that can be generated during the execution of the PGE, is contained in Appendix B.

#### 5.5.3.2 Status Log File: CER2.4P1_LogStatus_$SS2_$PS2_4_$CC2_4.yyyymmdd

The Status Log File contains all messages created by the Toolkit. If an abnormal exit is encountered by the PGE, this file should be examined for '_F_', fatal message type. The responsible person should be advised (see Table 1-1).

#### 5.5.3.3 User Log File: CER2.4P1_LogUser_$SS2_$PS2_4_$CC2_4.yyyymmdd

The User Log File is not used at this time, but exists to satisfy the Toolkit requirements. Typically the '_U_' and '_N_' (User information and Notice) will be written to the User Log File and the Status Log File.

### 5.5.4 Solutions to Possible Problems

If problems occur, consult the primary contact in Table 1-1.

### 5.5.5 Conditions for Subsystem and/or Target PGE(s) Terminal Failure (Halt all further processing)

a. Subsystem Termination

All output files are opened with status "NEW". If files exist, the program will terminate.

b. Target PGE Termination

Please refer to Appendix B for a descriptive list of all errors and the result of those errors. If .met files have not been created, the target PGE should not run. Target PGEs should not be processed in instances of PGE failure.

## 5.6 Expected Output Dataset(s)

(Note: Include all expected Web files.)
The expected output datasets are listed below for each instance of the PGE. This PGE is expected to run once per day.

Table 5-5. Expected Output File Listing for CER2.4P1

| File Name[a]/Directory | m/o[b] | File Size (MB) | Freq/ PGE | Target PGE | Destination[c] |
|---|---|---|---|---|---|
| CER2.4P1_PCF_$SS2_$PS2_4_$CC2_4.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.044 | 1/day | N/A | Archive rm |
| CER2.4P1_PCFin_$SS2_$PS2_4_$CC2_4.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.003 | 1/day | N/A | Archive rm |
| CER2.4P1_LogReport_$SS2_$PS2_4_$CC2_4.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.131 | 1/day | N/A | Archive rm |
| CER2.4P1_LogStatus_$SS2_$PS2_4_$CC2_4.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.102 | 1/day | N/A | Archive rm |
| CER2.4P1_LogUser_$SS2_$PS2_4_$CC2_4.yyyymmdd @($CERESHOME/erbelike/data/runlogs) | m | 0.099 | 1/day | N/A | Archive rm |
| CER_SCCD_$SS2_$PS2_4_$CC2_4.yyyymmdd (.met) @($CERESHOME/erbelike/data/ancillary/dynamic) | m | 0.543 | 1/day | CER2.2P1 CER2.3P1 CER2.3P2 CER4.5-6.1P2 | Archive |
| CER_SCCN_$SS2_$PS2_4_$CC2_4.yyyymmdd (.met) @($CERESHOME/erbelike/data/ancillary/dynamic) | m | 0.023 | 1/day | CER2.2P1 CER2.3P1 CER2.3P2 CER4.5-6.1P2 | Archive |
| SCCtrend_$SS2_ccctrend.web @($CERESHOME/erbelike/Web/scc_trend/data) | m | .001 | 1/instr | N/A | /QA, permanent, **NO ARCHIVE** |
| SCCtrend_log_$SS2.txt @($CERESHOME/erbelike/Web/scc_trend/data) | m | .001 | 1/instr | N/A | /QA, permanent, **NO ARCHIVE** |
| SCCtrend_plot_$SS2.gif @($CERESHOME/erbelike/Web/scc_trend/data) | m | .476 | 1/instr | N/A | /QA, permanent, **NO ARCHIVE** |

a. See Section 5.2 for information on variable data values.
If "(.met)" is written next to an expected output filename, then the metatdata file with the identical filename and .met extension must exist.
yyyy - 4-digit year (See Runtime Parameters Table 5-2)
mm - 2-digit month {valid values: 01 .. 12} (See Runtime Parameters Table 5-2)
dd - 2-digit day {valid values: 01 .. 31} (See Runtime Parameters Table 5-2)
ccc - spectral response channel designation { valid values: SW, TOT, TOT-SW, WN}

b. Note: m - mandatory output
o - optional output

c. Note: /QA - File is to be written to the DAAC designated /QA directory
rm - remove

## 5.7 Expected Temporary Files/Directories

Table 5-6. Temporary Files Listing for CER2.4P1

| Directory[a] | File Name |
|---|---|
| $CERESHOME/erbelike/data/scr/ CER2.4P1_$SS2_$PS2_4_$CC2_4.yyyymmdd | SRF_$SS2_SW.yyyymmdd |
| $CERESHOME/erbelike/data/scr/ CER2.4P1_$SS2_$PS2_4_$CC2_4.yyyymmdd | SRF_$SS2_TOT.yyyymmdd |
| $CERESHOME/erbelike/data/scr/ CER2.4P1_$SS2_$PS2_4_$CC2_4.yyyymmdd | SRF_$SS2_WN.yyyymmdd |

a. See Section 5.2 for information on variable data values.

# References

1. CERES Data Management System, Software Requirements Documents, Release 1, Version 1, January, 1995
2. CERES ERBE-like Averaging to Monthly TOA Fluxes (Subsystem 3.0) Operator's Manual.
3. Reference "Proposal for Semi-Automated Sampling Strategy, Production Strategy, and Configuration Code Implementation" internal paper for detail description of the CERES environment parameters. URL: http://asd-www.larc.nasa.gov/ceres/intern_doc/
4. Reference "DMT to DAAC Production Request." URL: http//asd-www.larc.nasa.gov/ceres/dmt2daac/

# Appendix A
# Acronyms and Abbreviations

| | |
|---|---|
| ASDC | Atmospheric Sciences Data Center |
| CERES | Clouds and the Earth's Radiant Energy System |
| CM | Configuration Management |
| DAAC | Distributed Active Archive Center |
| DB | Data Base |
| EOS | Earth Observing System |
| EOS-AM | EOS Morning Crossing Mission |
| EOS-PM | EOS Afternoon Crossing Mission |
| ERBE | Earth Radiation Budget Experiment |
| ERBS | Earth Radiation Budget Satellite |
| FAPS | Fixed Azimuth Plane Scan |
| FAPS+RAPS | Indicates FAPS and RAPS data processed together |
| FAPS, RAPS | Indicates FAPS and RAPS data processed separately |
| FOV | Field Of View |
| HDF | Hierarchical Data Format |
| LaRC | Langley Research Center |
| LaTIS | Langley TRMM Information System |
| LW | Longwave |
| MB | Megabytes |
| met | metadata file |
| μm | microns |
| N/A | Not Applicable |
| NASA | National Aeronautics and Space Administration |
| NOAA | National Oceanic and Atmospheric Administration |
| NSIDC | National Snow and Ice Data Center |
| PCF | Process Control File |
| PGE | Product Generation Executives |
| PSF | Point Spread Function |
| QC | Quality Control |
| RAPS | Rotating Azimuth Plane Scan |
| SAIC | Science Applications International Corporation |
| SMF | Status Message File |
| SW | Shortwave |
| TOA | Top-of-Atmosphere |

| | |
|---|---|
| TRMM | Tropical Rainfall Measuring Mission |
| VD | Validation Days |

# Appendix B
# Error Messages for Subsystem 2.0

Appendix B contains a list of messages that may be generated during the execution of PGEs CER2.1P1 through CER2.3P2. These messages are used to inform the operator or analyst of specific circumstances encountered during data processing. These messages may be strictly informative (Error Type = Status or Warning), or may indicate a fatal condition that results in premature PGE termination (Error Type = Fatal). All messages are written to the LogReport file of the processing instance.

Table B-1 contains a list of the PGE CER2.1P1 diagnostic messages. This table contains for each error the error message and error type, and the recommended action that should be taken when the message is encountered.

Table B-2 contains a list of the PGE CER2.2P1 diagnostic messages. This table contains for each error the error message content, the source module name, the error type, and the recommended action that should be taken when the message is encountered.

Table B-3 contains a list of the PGEs CER2.3P1 and CER2.3P2 diagnostic messages. This table contains for each error the error message content, the source module name, the error type, and the recommended action that should be taken when the message is encountered.

Table B-4 contains a list of the PGE CER2.4P1 diagnostic messages. This table contains for each error the error message, the error type, and the recommended action that should be taken when the message is encountered.

**Operator Instructions:**

If a PGE prematurely terminates, then take the following steps:

1. Look at the last few records on the LogStatus file.
2. Find the error message in the following Error Message listing(s), and follow the appropriate ACTION.
3. If an error message is not in the LogStatus File, then repeat steps 1 and 2 using the LogReport File.
4. If no information is derived, then call the responsible Subsystem Software Analyst[1].
5. If the appropriate ACTION failed, then call the responsible Subsystem Software Analyst[1].
6. In all cases, log all steps that were taken after the PGE failure, and send a copy to the responsible Subsystem Software Analyst[1].

1. Throughout this Appendix, "Subsystem Software Analyst" refers to the contact person found in Table 1-1 for PGEs CER2.1P1, CER2.2P1 - CER2.3P2, and CER2.4P1

Table B-1. PGE CER2.1P1 Error Messages (1 of 2)

| Message | Error Type | Action[a] |
|---|---|---|
| *Subroutine Name*(): Error ... Failed to close albedo file. | Fatal | A file listed in the PCF for logic IDs # 25 through 28 was not closed. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Failed to close iigs file. | Fatal | The file listed in the PCF for logic ID # 1000 was not closed. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Failed to read albedo file. | Fatal | A file listed in the PCF for logic IDs # 25 through 28 was not read. Verify that the file size is correct. |
| *Subroutine Name*(): Error ... Failed to write iigs file. | Fatal | The iigs data failed to write to the Snow PGE's output file listed in the PCF for logic ID # 1000. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... LW Threshold is out of range. | Fatal | The long wave data value is not within acceptable limits. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Month index is out of range. | Fatal | The software value for month contains an invalid number. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Unable to close file. | Fatal | A file listed in the PCF for logic ID # 15, 1001 or 1002 was not closed. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Unable to close PermSno file. | Fatal | A file listed in the PCF for logic ID # 13 or 16 was not closed. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Unable to close seasonal LW file. | Fatal | A file listed in the PCF for logic IDs # 30 through 33 was not closed. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Unable to close TempENV file. | Fatal | The file listed in the PCF for logic ID # 1003 was not closed. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Unable to get Month. | Fatal | The software was unable to retrieve the data month given in the PCF for logic ID # 10. Check the PCF ascii input file and PCF file for correctness. |
| *Subroutine Name*(): Error ... Unable to get Parameter. | Fatal | The software was unable to retrieve the parameter name given in the PCF for logic ID # 142, 143, or 148. Check the PCF ascii input file and PCF file for correctness. |
| *Subroutine Name*(): Error ... Unable to get Year. | Fatal | The software was unable to retrieve the data year given in the PCF for logic ID # 9. Check the PCF ascii input file and PCF file for correctness. |
| *Subroutine Name*(): Error ... Unable to open file. | Fatal | The file listed in the PCF for logic ID # 25 through 28, 30 through 33, or 1000 was not opened. Verify that file exists. Check the PCF ascii input file and PCF file for correctness. |
| *Subroutine Name*(): Error ... Unable to open Geobase file. | Fatal | The file listed in the PCF for logic ID # 15 was not opened. Verify that file exists. Check the PCF ascii input file and PCF file for correctness. |

Table B-1. PGE CER2.1P1 Error Messages (2 of 2)

| Message | Error Type | Action[a] |
|---|---|---|
| *Subroutine Name*(): Error ... Unable to open PermSno file. | Fatal | A file listed in the PCF for logic ID # 13 or 16 was not opened. Verify that file exists. Check the PCF ascii input file and PCF file for correctness. |
| *Subroutine Name*(): Error ... Unable to open TempENV file. | Fatal | The file listed in the PCF for logic ID # 1003 was not opened. Check the PCF ascii input file and PCF file for correctness. |
| *Subroutine Name*(): Error ... Unable to read Min NSIDC files. | Fatal | The minimum number of files listed in the PCF for logic IDs # 201 through 231 was not read. Verify that file exists. Check the PCF ascii input file and PCF file for correctness. |
| *Subroutine Name*(): Error ... Unable to read PermSno file. | Fatal | A file listed in the PCF for logic ID # 13 or 16 was not read. Verify that the file size is correct. |
| *Subroutine Name*(): Error ... Unable to read seasonal LW file. | Fatal | A file listed in the PCF for logic IDs # 30 through 33 was not read. Verify that the file size is correct. |
| *Subroutine Name*(): Error ... Unable to write to fmt file. | Fatal | The iigs data failed to write to the Snow PGE's output file listed in the PCF for logic ID # 1001. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Unable to write to TempENV file. | Fatal | The temporary data failed to write to the Snow PGE's output file listed in the PCF for logic ID # 1003. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Error ... Unable to write to web file. | Fatal | The iigs data failed to write to the Snow PGE's output file listed in the PCF for logic ID # 1002. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Warning ... Unable to close QC file. | Warning | The file listed in the PCF for logic ID # 900 was not closed. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Warning ... Unable to open QC file. | Warning | The file listed in the PCF for logic ID # 900 was not opened. Check the PCF ascii input file and PCF file for correctness. |
| *Subroutine Name*(): Warning ... Unable to write to QC file. | Warning | The QC report data failed to write to the Snow PGE's output file listed in the PCF for logic ID # 900. Contact the Subsystem Software Analyst. |
| *Subroutine Name*(): Warning ... Unable to read NSIDC file. | Warning | A file listed in the PCF for logic IDs # 201 through 231 was not read. Verify that file exists. Check the PCF ascii input file and PCF file for correctness. |

a. In this table, "Subsystem Software Analyst" refers to the contact person found in Table 1-1.

Variables used in Table B-2, Table B-3, and Table B-4 and in the following Action Item Codes are defined as follows:

| | |
|---|---|
| yyyy | = 4-digit CERDataDateYear (> 1996) |
| mm | = 2-digit CERDataDateMonth (1 .. 12) |
| dd | = 2-digit CERDataDateDay (01 .. 31) |
| nn | = 01 .. 36 |

The following are Action Item Codes. These codes appear in the Action column of Table B-2, Table B-3 and Table B-4 as bold type. For more information on input and output file names, refer to Appendix C.

A. Verify ancillary input namelist file, NIPSC, is valid. (PCF Logic ID = 40)
B. Verify SNOW input file is valid. (PCF Logic ID = 43)
C. Verify CXDR file is valid. (PCF Logic ID = 240)
D. Verify PLTF file is valid. (PCF Logic ID = 101 - 136)
E. Verify PSCHSK file is valid. (PCF Logic ID = 137)
F. Verify PRES8 input file is valid. (PCF Logic ID = 22)
G. Verify PRES8 input header is valid. (PCF Logic ID = 22)

a. See error message file for further information.
b. See QC report for further information.
c. Notify Primary Contact from Table 1-1.

Table B-2. PGEs CER2.2P1 Error Messages (1 of 5)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| MESSAGE NUMBER : 100<br>strt5(): Notice ... No Valid FAPS Alongtrack Data to Process. | inv | Notice | None |
| MESSAGE NUMBER : 100<br>strt5(): Notice ... No Valid FAPS Crosstrack Data to Process. | inv | Notice | None |
| MESSAGE NUMBER : 100<br>strt5(): Notice ... No Valid RAPS Data to Process. | inv | Notice | None |
| MESSAGE NUMBER : 101<br>Error ... Matching Instrument Name Supplied in PCF. | inv | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Error Message File. | inv | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Output EID-6 File. | inv | Fatal | **(a**,c**)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Namelist File. | inv | Fatal | **(A,a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening PRE-ES8 or ES8 File. | inv | Fatal | If ES-8 file is used as input, verify its validity. **(F,a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening QC Report File. | inv | Fatal | Verify output QC-7 Report is valid. (PCF Logic ID = 53) **(a,c)** |

Table B-2. PGEs CER2.2P1 Error Messages (2 of 5)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Scene Identification File. | inv | Fatal | Verify binary seasonally varying scene ID files BIILW are valid. Verify binary temporally invariant scene ID file BIISW02 is valid. (PCF Logic ID = 45 - 49) **(B,a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Spectral Correction File. | inv | Fatal | Verify ancillary input spectral correction file NIISC is valid. (PCF Logic ID = 31) **(a,c)** |
| MESSAGE NUMBER : 101<br>scinv(): Error ... Opening Output ES8N File. | inv | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>toolkit_open(): Error ... Opening Spec_Corr Coeff File. | si_spcor | Fatal | Verify ancillary input spectral correction file is valid. (PCF Logic ID = 61 and 62) **(a,c)** |
| MESSAGE NUMBER : 101<br>gen_pres8(): Error ... Opening PRES8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>gen_pres8(): Error ... Opening S-8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>gen_pres8(): Error ... Opening Temp File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>getoffs(): Error ... Opening Offset File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>strt5(): Error ... Reading Spectral Correction File. | inv | Fatal | **(F,a,c)** |
| MESSAGE NUMBER : 102<br>patvfy(): Error ... Reading PRE-ES8 File Header. | inv | Fatal | **(G,a,c)** |
| MESSAGE NUMBER : 102<br>reader() : Error ... Reading Input Data File. | inv | Fatal | **(F,a,c)** |
| MESSAGE NUMBER : 102<br>valscan(): Error ... Reading ES8 File. | inv | Fatal | Verify ES-8 file is valid. (PCF Logic ID = 701) **(a,c)** |
| MESSAGE NUMBER : 102<br>si_begin(): Error ... Reading Spec_Corr Coeff File. | si_spcor | Fatal | **(F,a,c)** |
| MESSAGE NUMBER : 102<br>gen_pres8(): Error ... Reading Scale Factors. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>getoffs(): Error ... Reading Offset File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>gbfhed(): Error ... Reading Header Information. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>getrec(): Error ... Reading Temp File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>getrec(): Error ... Reading S-8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 103<br>scinv(): Error ... Writing Output ES8N File. | inv | Fatal | **(a,c)** |
| MESSAGE NUMBER : 103<br>nadir_write(): Error ... Writing ES8 Nadir Scan File. | nadir_util | Fatal | **(a,c)** |
| MESSAGE NUMBER : 103<br>gen_pres8(): Error ... Writing Temp File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>si_begin(): Error ... Closing Spec_Corr Coeff File. | si_spcor | Fatal | **(a,c)** |

Table B-2. PGEs CER2.2P1 Error Messages (3 of 5)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| MESSAGE NUMBER : 104<br>gen_pres8(): Error ... Closing PRES8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>gen_pres8(): Error ... Closing S-8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>getoffs(): Error ... Closing Offset File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>gen_pres8(): Error ... Closing Temp File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 113<br>gen_pres8(): Notice ... NOAA9 Offsets applied. | gen_pres8 | Notice | Verify spacecraft equals "NOAA9"<br>(PCF Logic ID = 503) |
| MESSAGE NUMBER : 114<br>strt5(): Notice ... EID6 Output Flag is Turned OFF. | inv | Notice | Verify iscout in PCF equals the file ID for the EID-6 file.<br>(PCF Logic ID = 651) **(a,c)** |
| MESSAGE NUMBER : 122<br>strt5(): Notice ... ES8 Output Flag is Turned OFF. | inv | Notice | Verify i12out in PCF equals the file ID for the ES-8 file.<br>(PCF Logic ID = 652) **(a,c)** |
| MESSAGE NUMBER : 130<br>patvfy(): Error ... SS Indicator and/or the Product Code Not Verified. | inv | Fatal | **(A,G,a,c)** |
| MESSAGE NUMBER : 138<br>chkreq():Error ... Reading data date or spacecraft. | inv | Fatal | Verify data date and spacecraft are correct in PCF.<br>(PCF Logic ID = 601 - 607) **(G,a,c)** |
| MESSAGE NUMBER : 138<br>gen_pres8(): Error ... Failed to Get Data Date. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 138<br>gen_pres8(): Error ... Failed to Get Scft Code. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 141<br>gen_pres8(): Error ... Failed to Get Record. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 142<br>gen_pres8(): Error ... Failed to Get Offsets. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 148<br>rdati(): Error ... EOF Read During Initial Read Attempt. | inv | Fatal | **(F,a,c)** |
| MESSAGE NUMBER : 215<br>scinv(): Warning ... Failed to process nadir scan. | inv | Warning | None |
| MESSAGE NUMBER : 216<br>rdpat(): Error ... ES8 Data Not Chronologically Sequenced. | inv | Fatal | **(A,F,a,c)** |
| MESSAGE NUMBER : 218<br>swzeroe(): Warning ... IORB Greater Than 15. | inv | Warning | None |
| MESSAGE NUMBER : 219<br>spcor_new(): Error ... Invalid Scene Type. | inv | Fatal | **(B,a,c)** |
| MESSAGE NUMBER : 221<br>spcor_new(): Error ... Invalid Scene Type. | inv | Fatal | Verify ancillary input spectral correction file NIISC is valid. (PCF Logic ID = 31) **(a,c)** |
| MESSAGE NUMBER : 222<br>scnid(): Error ... Cloud Cover Index Cannot be Determined. | inv | Fatal | Verify binary seasonally varying scene ID files BIILW are valid. Verify binary temporally invariant scene ID file BIISW02 is valid.<br>(PCF Logic ID = 45 - 49) **(A,B,F,a,c)** |
| MESSAGE NUMBER : 223<br>scacum(): Notice ... Opening a Second 2.5-DEG Active Scanner Region. | inv | Notice | None. **(a)** |
| MESSAGE NUMBER : 224<br>scacum(): Error ... No More Active Region Storage. | inv | Fatal | **(a,c)** |

Table B-2. PGEs CER2.2P1 Error Messages (4 of 5)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| MESSAGE NUMBER : 230<br>scacum(): Error ... Scanner Region Indexing Problem. | inv | Fatal | **(a,c)** |
| MESSAGE NUMBER : 540<br>geoscn(): Error ... Invalid Scene Type. | inv | Fatal | **(B,a,c)** |
| pgspci(): Error ... Getting PC Parameter Value. | inv | Fatal | Verify PCF is valid - the module is trying to retrieve a particular parameter. **(a,c)** |
| maines8(): Error ... SWopen Failed | ConvertES8 | Fatal | HDF function swopen cannot open ES-8 HDF-EOS file. Verify file exists and is valid. (PCF Logic ID = 701) **(c)** |
| maines8(): Error ... SWcreate Failed | ConvertES8 | Fatal | HDF function swcreate cannot create a swath for the ES-8 HDF-EOS file.**(c)** |
| maines8(): Error ... SWdefdim Failed | ConvertES8 | Fatal | HDF function swdefdim cannot define a dimension within the newly created swath. **(c)** |
| maines8(): Error ... SWdefgfld Failed | ConvertES8 | Fatal | HDF function swdefgfld cannot define a geolocation field within the newly created swath. **(c)** |
| maines8(): Error ... SWdefdfld Failed | ConvertES8 | Fatal | HDF function swdefdfld cannot define a data field within the newly created swath. **(c)** |
| maines8(): Error ... SWdetach Failed | ConvertES8 | Fatal | HDF function swdetach cannot close the newly created swath. **(c)** |
| maines8(): Error ... SWclose Failed | ConvertES8 | Fatal | HDF function swclose cannot close the ES-8 HDF-EOS file. **(c)** |
| maines8(): Error ... Writing 64-Bit VData | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Writing 32-Bit VData | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Writing SDS Data | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Writing Measurement Flag Words | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Writing Scanner Operation Flag Words | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Attaching Swath Failed | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Sfstart Failed | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Writing Units | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Writing Range | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Writing Fill Value | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Hopen Failed | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Closing File | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Vsfdtch Failed | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Hclose Failed | ConvertES8 | Fatal | **(a,c)** |
| maines8(): Error ... Opening ES8 File | MainES8 | Fatal | Cannot open ES-8 Binary file. Verify file exists and is valid. **(c)** |
| maines8(): Error ... GetFileName for HDF output File | MainES8 | Fatal | Error retrieving output filename from PCF. Verify PCF. **(c)** |
| maines8(): Error ... Reading data from binary ES-8 FileReading ES8 File | MainES8 | Fatal | Cannot read ES-8 Binary file. Verify file exists and is valid. (PCF Logic ID = 701) **(c)** |

Table B-2. PGEs CER2.2P1 Error Messages (5 of 5)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| read_qc(): Error ... Closing ERBE-like Monthly QC. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Unable to close eMail subject file. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Unable to close Bad Data file. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Unable to close QCcheck.list file. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Failed to get filename using Logic ID. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Unable to open eMail subject file. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Opening ERBE-like Monthly QC Report. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Opening ERBE-like QC Checklist file. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Opening ERBE-like QC Bad Data file. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Unable to read QCcheck.list file. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Read_row_col failed. | read_qc | Fatal | **(a**,c**)** |
| read_qc(): Error ... Row in QCcheck list is too large. | read_qc | Fatal | **(a**,c**)** |

Table B-3. PGEs CER2.3P1 - CER2.3P2 Error Messages (1 of 4)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| MESSAGE NUMBER : 100<br>strt5(): Notice ... No Valid FAPS Alongtrack Data to Process. | inv | Notice | None |
| MESSAGE NUMBER : 100<br>strt5(): Notice ... No Valid FAPS Crosstrack Data to Process. | inv | Notice | None |
| MESSAGE NUMBER : 100<br>strt5(): Notice ... No Valid RAPS Data to Process. | inv | Notice | None |
| MESSAGE NUMBER : 101<br>inutil(): Error ... Opening Error Message File. | inv | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Namelist File. | inv | Fatal | **(A,a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Output EID-6 File. | inv | Fatal | **(a**,c**)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening PRE-ES8 or ES8 File. | inv | Fatal | If ES-8 file is used as input, verify its validity. (PCF Logic ID = 22) **(F,a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening QC Report File. | inv | Fatal | Verify output QC-7 Report is valid. (PCF Logic ID = 53) **(a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Scene Identification File. | inv | Fatal | Verify binary seasonally varying scene ID files BIILW are valid. Verify binary temporally invariant scene ID file BIISW02 is valid. (PCF Logic ID = 45 - 49) **(B,a,c)** |
| MESSAGE NUMBER : 101<br>strt5(): Error ... Opening Spectral Correction File. | inv | Fatal | Verify ancillary input spectral correction file NIISC is valid. (PCF Logic ID = 31) **(a,c)** |
| MESSAGE NUMBER : 101<br>toolkit_open(): Error ... Opening Spec_Corr Coeff File. | si_spcor | Fatal | Verify ancillary input spectral correction file is valid. (PCF Logic ID = 61 and 62) **(a,c)** |
| MESSAGE NUMBER : 101<br>gen_pres8(): Error ... Opening PRES8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>gen_pres8(): Error ... Opening S-8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>gen_pres8(): Error ... Opening Temp File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>getoffs(): Error ... Opening Offset File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>patvfy(): Error ... Reading PRE-ES8 File Header. | inv | Fatal | **(G,a,c)** |
| MESSAGE NUMBER : 102<br>reader(): Error ... Reading Input Data File. | inv | Fatal | **(F,a,c)** |
| MESSAGE NUMBER : 102<br>valscan(): Error ... Reading ES8 File. | inv | Fatal | Verify ES-8 file is valid. **(a,c)** |
| MESSAGE NUMBER : 102<br>si_begin(): Error ... Reading Spec_Corr Coeff File. | si_spcor | Fatal | **(F,a,c)** |
| MESSAGE NUMBER : 102<br>gen_pres8(): Error ... Reading Scale Factors. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>getoffs(): Error ... Reading Offset File. | gen_pres8 | Fatal | **(a,c)** |

Table B-3. PGEs CER2.3P1 - CER2.3P2 Error Messages (2 of 4)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| MESSAGE NUMBER : 102<br>gbfhed(): Error ... Reading Header Information. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>getrec(): Error ... Reading Temp File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>getrec(): Error ... Reading S-8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 103<br>gen_pres8(): Error ... Writing Temp File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>si_begin(): Error ... Closing Spec_Corr Coeff File. | si_spcor | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>gen_pres8(): Error ... Closing PRES8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>gen_pres8(): Error ... Closing S-8 data file. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>getoffs(): Error ... Closing Offset File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>gen_pres8(): Error ... Closing Temp File. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 113<br>gen_pres8(): Notice ... NOAA9 Offsets applied. | gen_pres8 | Notice | Verify spacecraft equals "NOAA9"<br>(PCF Logic ID = 503) |
| MESSAGE NUMBER : 114<br>strt5(): Notice ... EID6 Output Flag is Turned OFF. | inv | Notice | Verify iscout in PCF equals the file ID for the EID-6 file.<br>(PCF Logic ID = 651) **(a,c)** |
| MESSAGE NUMBER : 122<br>strt5(): Notice ... ES8 Output Flag is Turned OFF. | inv | Notice | Verify i12out in PCF equals the file ID for the ES-8 file.<br>(PCF Logic ID = 652) **(a,c)** |
| MESSAGE NUMBER : 123<br>strt5(): Notice ... ES8N Output Flag is Turned OFF. | inv | Notice | Verify nadir_unit in PCF equals the file ID for the ES-8 nadir file. (PCF Logic ID = 653) **(a,c)** |
| MESSAGE NUMBER : 130<br>patvfy(): Error ... SS Indicator and/or the Product Code Not Verified. | inv | Fatal | **(A,G,a,c)** |
| MESSAGE NUMBER : 138<br>chkreq(): Error ... Reading data date or spacecraft. | inv | Fatal | Verify data date and spacecraft are correct in PCF.<br>(PCF Logic ID = 601 - 607) **(G,a,c)** |
| MESSAGE NUMBER : 138<br>gen_pres8(): Error ... Failed to Get Data Date. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 138<br>gen_pres8(): Error ... Failed to Get Scft Code. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 141<br>gen_pres8(): Error ... Failed to Get Record. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 142<br>gen_pres8(): Error ... Failed to Get Offsets. | gen_pres8 | Fatal | **(a,c)** |
| MESSAGE NUMBER : 148<br>rdati(): Error ... EOF Read During Initial Read Attempt. | inv | Fatal | **(F,a,c)** |
| MESSAGE NUMBER : 216<br>rdpat(): Error ... ES8 Data Not Chronologically Sequenced. | inv | Fatal | **(A,F,a,c)** |
| MESSAGE NUMBER : 218<br>swzero(): Warning ... IORB Greater Than 15. | inv | Warning | None |

Table B-3. PGEs CER2.3P1 - CER2.3P2 Error Messages (3 of 4)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| MESSAGE NUMBER : 219<br>spcor_new(): Error ... Invalid Scene Type. | inv | Fatal | **(B,a,c)** |
| MESSAGE NUMBER : 221<br>spcor_new(): Error ... Invalid Scene Type. | inv | Fatal | Verify ancillary input spectral correction file NIISC is valid. (PCF Logic ID = 31) **(a,c)** |
| MESSAGE NUMBER : 222<br>scnid(): Error ... Cloud Cover Index Cannot be Determined. | inv | Fatal | Verify binary seasonally varying scene ID files BIILW are valid. Verify binary temporally invariant scene ID file BIISW02 is valid. (PCF Logic ID = 45 - 49) **(A,B,F,a,c)** |
| MESSAGE NUMBER : 223<br>scacum(): Notice ... Opening a Second 2.5-DEG Active Scanner Region. | inv | Notice | None. **(a)** |
| MESSAGE NUMBER : 224<br>scacum(): Error ... No More Active Region Storage. | inv | Fatal | **(a,c)** |
| MESSAGE NUMBER : 230<br>scacum(): Error ... Scanner Region Indexing Problem. | inv | Fatal | **(a,c)** |
| MESSAGE NUMBER : 540<br>geoscn(): Error ... Invalid Scene Type. | inv | Fatal | **(B,a,c)** |
| pgspci(): Error ... Getting PC Parameter Value. | inv | Fatal | Verify PCF is valid - the module is trying to retrieve a particular parameter. **(a,c)** |
| MESSAGE NUMBER : 1<br>ddbint():Error ... Opening House Keeping File. | ddbint | Fatal | **(E,a,c)** |
| MESSAGE NUMBER : 3<br>ddbint(): Error ... Writing House Keeping File. | ddbint | Fatal | **(E,a,c)** |
| MESSAGE NUMBER : 3<br>sinhsk(): Error ... Writing House Keeping File. | ddbint | Fatal | **(E,a,c)** |
| pgspci(): Error ... Getting PC Parameter Value. | ddbint | Fatal | Verify PCF is valid - the module is trying to retrieve a particular parameter. **(a,c)** |
| MESSAGE NUMBER : 9024<br>regrep(): Warning ... Error Resolution. | ddbint | Warning | **(a,c)** |
| MESSAGE NUMBER : 1<br>suopdb(): Error ... Opening House Keeping File. | ddbupd | Fatal | **(E,a,b,c)** |
| MESSAGE NUMBER : 1<br>suopdb(): Error ... Opening Latitude File. | ddbupd | Fatal | **(B,a,b,c)** |
| MESSAGE NUMBER : 1<br>suopdb(): Error ... Opening Overlap File. | ddbupd | Fatal | **(C,a,b,c)** |
| MESSAGE NUMBER : 1<br>suopin(): Error ... Opening Inversion EID6 File. | ddbupd | Fatal | Verify the EID-6 file is valid. (PCF Logic ID = 301) **(a,b,c)** |
| MESSAGE NUMBER : 1<br>suwrep(): Error ... Opening QC Report File. | ddbupd | Fatal | Verify the QC Report is valid. (PCF Logic ID = 250) **(a,b,c)** |
| MESSAGE NUMBER : 2<br>sucldb(): Error ... Reading House Keeping File. | ddbupd | Fatal | **(E,a,b,c)** |
| MESSAGE NUMBER : 2<br>suopdb(): Error ... Reading House Keeping File. | ddbupd | Fatal | **(E,a,b,c)** |
| MESSAGE NUMBER : 3<br>sucldb(): Error ... Writing House Keeping File. | ddbupd | Fatal | **(E,a,b,c)** |
| MESSAGE NUMBER : 3<br>sucldb(): Error ... Writing Overlap File. | ddbupd | Fatal | **(C,a,b,c)** |

Table B-3. PGEs CER2.3P1 - CER2.3P2 Error Messages (4 of 4)

| Message | Module Name | Error Type | Action |
|---|---|---|---|
| MESSAGE NUMBER : 3<br>suscan(): Error ... Writing Latitude File. | ddbupd | Fatal | **(D,a,b,c)** |
| MESSAGE NUMBER : 3<br>suscan(): Error ... Writing Overlap File. | ddbupd | Fatal | **(C,a,b,c)** |
| MESSAGE NUMBER : 6<br>suscan(): Warning ... Region Number out of Range. | ddbupd | Warning | Program continues to process the next record. **(a,b)** |
| MESSAGE NUMBER : 8<br>suopdb(): Error ... Overlap Data Already Processed. | ddbupd | Fatal | **(E,a,c)** |
| MESSAGE NUMBER : 16<br>suopdb(): Error ... Opening Latitude File. | ddbupd | Fatal | This error will accompany one or more of the "MESSAGE 1 FROM SUOPDB: ERROR OPENING LATITUDINAL FILE PLTFnn" error messages. Follow the recommended action for them.<br>(PCF Logic ID = 101 - 136) **(c)** |
| MESSAGE NUMBER : 301<br>suscan(): Error ... Reading Inversion EID6 File. | ddbupd | Fatal | Verify the EID-6 file is valid. (PCF Logic ID = 301) **(a,b,c)** |
| pgspci(): Error ... Getting PC Parameter Value. | ddbupd | Fatal | Verify PCF is valid - the module is trying to retrieve a particular parameter. **(a,c)** |
| MESSAGE NUMBER : 9024<br>regrep(): Warning ... Error Resolution. | ddbupd | Warning | **(a,c)** |

Table B-4. PGEs CER2.4P1 Error Messages (1 of 2)

| Message | Error Type | Action |
|---|---|---|
| *Subroutine Name*():Notice ... Beginning of scc software. | Notice | None |
| Subroutine Name():Error ... Cannot process singular matrix. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 100<br>*Subroutine Name*(): Error ... Incorrect input. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 100<br>*Subroutine Name*(): Error ... Input command line argument incorrect. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 100<br>*Subroutine Name*(): Error ... Failed to get interpolation interval. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 100<br>*Subroutine Name*(): Error ... Character was not converted to number. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 101<br>*Subroutine Name*(): Error ... Opening Spectral Response File. | Fatal | Verify output QC-7 Report is valid. (PCF Logic ID = 53) **(a,c)** |
| MESSAGE NUMBER : 101<br>*Subroutine Name*(): Error ... Opening Modtran File (*tp7) | Fatal | Verify ancillary input file is valid. (PCF Logic IDs = 2001 - 2030) **(a,c)** |
| MESSAGE NUMBER : 101<br>*Subroutine Name*(): Opening Coef File (*coef) | Fatal | Verify intermediate coeficient file is valid. (PCF Logic IDs = 3001 - 3180) **(a,c)** |
| MESSAGE NUMBER : 101<br>*Subroutine Name*(): Error ... Opening Regression File (*regr) | Fatal | Verify intermediate regression file is valid. (PCF Logic ID = 4001 - 4188) **(a,c)** |
| MESSAGE NUMBER : 101<br>*Subroutine Name*(): Error ... Opening Regression Out File (*regr*.out) | Fatal | Verify intermediate regression file is valid. (PCF Logic ID = 4001 - 4188) **(a,c)** |
| MESSAGE NUMBER : 102<br>*Subroutine Name*(): Error ... Reading Coef File (*coef) | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>*Subroutine Name*(): Error ... Reading Spectral Response File. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 102<br>*Subroutine Name*(): Error ... Reading Modtran File (*tp7) | Fatal | **(a,c)** |
| MESSAGE NUMBER : 103<br>*Subroutine Name*(): Error ... Writing Coef File (*coef) | Fatal | **(a,c)** |
| MESSAGE NUMBER : 103<br>*Subroutine Name*(): Error ... Writing Regression File (*regr) | Fatal | **(a,c)** |
| MESSAGE NUMBER : 103<br>*Subroutine Name*(): Error ... Writing Regression Out File (*regr*.out) | Fatal | **(a,c)** |
| MESSAGE NUMBER : 103<br>*Subroutine Name*(): Error ... Writing Spectral Response File. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>*Subroutine Name*(): Error ... Closing Spectral Response File. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>*Subroutine Name*(): Error ... Closing Modtran File (*tp7). | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>*Subroutine Name*(): Error ... Closing Coef File (*coef). | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>*Subroutine Name*(): Error ... Closing Regression File (*regr) | Fatal | **(a,c)** |
| MESSAGE NUMBER : 104<br>*Subroutine Name*(): Error ... Closing Regression Out File (*regr*.out) | Fatal | **(a,c)** |

Table B-4. PGEs CER2.4P1 Error Messages (2 of 2)

| Message | Error Type | Action |
|---|---|---|
| MESSAGE NUMBER : 112<br>Subroutine Name(): Error ... File Header doesnot match intrument. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 113<br>Subroutine Name(): Error ... File Header doesnot match channel. | Fatal | **(a,c)** |
| MESSAGE NUMBER : 114<br>Subroutine Name(): Error ... File Header doesnot match interpolation date. | Fatal | **(a,c)** |

# Appendix C
# Sample ASCII (PCFin) File Listing(s) for Subsystem 2.0

## Sample ASCII (PCFin) File Listing(s) for PGE CER2.1P1

```
###########################
# CERES baseline Metadata
###########################
CERPGEName = CER2.1P1
SamplingStrategy = CERES
ProductionStrategy = Test
CERDataDateYear = 2000
CERDataDateMonth = 03
ConfigurationCode = 000000
SWsccr = 000
DATAsccr = 000

##################################
# PGE specific runtime parameters
##################################
Satellite_Platform = NSIDC
Satellite_Instrument = DMSP
Satellite_Sensor = SSM/I

#################################
# PCF required directories
#################################
SS2.1_InputDir.1 = /CERES/erbelike/data/input/
SS2.1_InputDir.2 = /CERES/erbelike/data/ancillary/static/
SS2.1_OutputDir.1 = /CERES/erbelike/data/ancillary/static/
SS2.1_OutputDir.2 = /CERES/erbelike/data/out_comp/data/snow/
SS2.1_OutputDir.3 = /CERES/erbelike/Web/snow/data/
SS2.1_OutputDir.4 = /CERES/erbelike/data/scr/CER2.1P1_CERES_Test_000000.200003
SS2.1_OutputDir.5 = /CERES/erbelike/Web/qc/snow/
SS2.1_OutputDir.6 = /CERES/erbelike/data/ancillary/dynamic/
SS2.1_RunDir =  /CERES/erbelike/bin/
SS2.1_LogsDir =   /CERES/erbelike/data/runlogs/
SS2.1_MCFDir = /CERES/erbelike/rcf/mcf/

##################################
# Input file names
##################################
SS2.1_Inputfile.h = psnow.map.19971231
SS2.1_Inputfile.a = SNOW_COMPOSITE_03.19980130
SS2.1_Inputfile.b = indx_EASE_dat.19971101
```

**SS2.1_Inputfile.c = baseline.map.19971101**
**SS2.1_Inputfile.g = CCSNOWAA.mcf**
**SS2.1_Inputfile.i = CCQCR_AA.mcf**

## Sample Input File Listing for PGE CER2.1P1 - CONT'

**SS2.1_Inputfile.01 = NISE_SSMIF13_20000301.HDFEOS**
**SS2.1_Inputfile.02 = NISE_SSMIF13_20000302.HDFEOS**
**SS2.1_Inputfile.03 = NISE_SSMIF13_20000303.HDFEOS**
**SS2.1_Inputfile.04 = NISE_SSMIF13_20000304.HDFEOS**
**SS2.1_Inputfile.05 = NISE_SSMIF13_20000305.HDFEOS**
**SS2.1_Inputfile.06 = NISE_SSMIF13_20000306.HDFEOS**
**SS2.1_Inputfile.07 = NISE_SSMIF13_20000307.HDFEOS**
**SS2.1_Inputfile.08 = NISE_SSMIF13_20000308.HDFEOS**
**SS2.1_Inputfile.09 = NISE_SSMIF13_20000309.HDFEOS**
**SS2.1_Inputfile.10 = NISE_SSMIF13_20000310.HDFEOS**
**SS2.1_Inputfile.11 = NISE_SSMIF13_20000311.HDFEOS**
**SS2.1_Inputfile.12 = NISE_SSMIF13_20000312.HDFEOS**
**SS2.1_Inputfile.13 = NISE_SSMIF13_20000313.HDFEOS**
**SS2.1_Inputfile.14 = NISE_SSMIF13_20000314.HDFEOS**
**SS2.1_Inputfile.15 = NISE_SSMIF13_20000315.HDFEOS**
**SS2.1_Inputfile.16 = NISE_SSMIF13_20000316.HDFEOS**
**SS2.1_Inputfile.17 = NISE_SSMIF13_20000317.HDFEOS**
**SS2.1_Inputfile.18 = NISE_SSMIF13_20000318.HDFEOS**
**SS2.1_Inputfile.19 = NISE_SSMIF13_20000319.HDFEOS**
**SS2.1_Inputfile.20 = NISE_SSMIF13_20000320.HDFEOS**
**SS2.1_Inputfile.21 = NISE_SSMIF13_20000321.HDFEOS**
**SS2.1_Inputfile.22 = NISE_SSMIF13_20000322.HDFEOS**
**SS2.1_Inputfile.23 = NISE_SSMIF13_20000323.HDFEOS**
**SS2.1_Inputfile.24 = NISE_SSMIF13_20000324.HDFEOS**
**SS2.1_Inputfile.25 = NISE_SSMIF13_20000325.HDFEOS**
**SS2.1_Inputfile.26 = NISE_SSMIF13_20000326.HDFEOS**
**SS2.1_Inputfile.27 = NISE_SSMIF13_20000327.HDFEOS**
**SS2.1_Inputfile.28 = NISE_SSMIF13_20000328.HDFEOS**
**SS2.1_Inputfile.29 = NISE_SSMIF13_20000329.HDFEOS**
**SS2.1_Inputfile.30 = NISE_SSMIF13_20000330.HDFEOS**
**SS2.1_Inputfile.31 = NISE_SSMIF13_20000331.HDFEOS**
**SS2.1_Inputfile.3a = combspr.19980130**
**SS2.1_Inputfile.3b = combsum.19980130**
**SS2.1_Inputfile.3c = combaut.19980130**
**SS2.1_Inputfile.3d = combwin.19980130**
**SS2.1_Inputfile.4a = BIILWAT.19980130**
**SS2.1_Inputfile.4b = BIILWSM.19980130**
**SS2.1_Inputfile.4c = BIILWSP.19980130**
**SS2.1_Inputfile.4d = BIILWWN.19980130**

## Sample Input File Listing for PGE CER2.1P1 - CONT'

```
#####################################
# Output file names
#####################################
SS2.1_Outputfile.1 = CER_SNOW_CERES_Test_000000.200003
SS2.1_Outputfile.2 = CER_CQCR_CERES_Test_000000.200003
SS2.1_Outputfile.3 = CERESweb_200003.map
SS2.1_Outputfile.4 = CERESfmt_200003.map
SS2.1_Outputfile.5 = CERESscr_200003.gif
SS2.1_Outputfile.6 = CEREScqcrw_200003.txt
SS2.1_Outputfile.7 = TempENV.dat
SS2.1_Outputfile.8 = TempSNOW.ps

#####################################
# Log file names
#####################################
SS2.1_Logsfile.1 = CER2.1P1_LogStatus_CERES_Test_000000.200003
SS2.1_Logsfile.2 = CER2.1P1_LogReport_CERES_Test_000000.200003
SS2.1_Logsfile.3 = CER2.1P1_LogUser_CERES_Test_000000.200003
```

# Sample Input File Listing for PGE CER2.2P1

```
#  METADATA RUN-TIME PARAMETERS

PGEName = CER2.2P1
SamplingStrategy = Terra-FM1
ProductionStrategy = Test
CERDataDateYear = 2000
CERDataDateMonth = 03
CERDataDateDay = 15
ConfigurationCode = 000000
SWsccr = 000
DATAsccr = 000


#  I/O DIRECTORIES

tkrdir = /opt/net/TK5.2.7v1/TOOLKIT/runtime
tkddir = /opt/net/TK5.2.7v1/TOOLKIT/database
clddir = /CERES/lib/sgi64_lib/data
rcfdir = /CERES/erbelike/rcf/pcf
mcfdir = /CERES/erbelike/rcf/mcf
scrdir = /CERES/erbelike/data/scr/CER2.2_Terra-FM1_Test_000000.20000315
ancdir = /CERES/erbelike/data/ancillary/static
dyndir = /CERES/erbelike/data/ancillary/dynamic
logdir = /CERES/erbelike/data/runlogs
wqcdir = /CERES/erbelike/Web/qc/inv
gifdir = /CERES/erbelike/Web/graphics/ES8/gif/ES8_200003_2/ES8_20000315_2
inpdir = /CERES/instrument/data/out_comp
invdir = /CERES/erbelike/data/out_comp/data/inv


#  ANCILLARY INPUT FILES

ancfile1 = NIISCOLD.19980904
DAY = ceres_SI_FM1_day.20000804
NIGHT = ceres_SI_FM1_night.20000804
TOLERANCES = map_FM1_fullscan.20010612
ancfile2 = NIPSC.19991123
ancfile3 = CER_SNOW_CERES_Test_000000.200003
ancfile4 = BIISW02.19980130
ancfile5 = BIILWSP.19980130
```

## Sample Input File Listing for PGE CER2.2P1- CONT'

**# I/O FILES**

**inpfile1 = CER_PRES8_Terra-FM1_Edition1_017012.20000315**
**inpfileqc1 = CER_CQCIM_Terra-FM1.200105**
**inpfileqc2 = CER_CQCIM_Terra-FM1.200104**
**inpfileqc3 = CER_CQCIM_Terra-FM1.200103**

**outfile1 = CER_CMSG_Terra-FM1_Test_000000.20000315**
**outfile2 = CER_CQCI_Terra-FM1_Test_000000.20000315**
**outfile3 = CER_EID6_Terra-FM1_Test_000000.20000315**
**outfile4 = CER_ES8N_Terra-FM1_Test_000000.20000315**
**outfile5 = CER_ES8B_Terra-FM1_Test_000000.20000315**
**outfile6 = CER_ES8_Terra-FM1_Test_000000.20000315**
**outfileqc = CER_CQCIM_Terra-FM1.200003**
**giffile1 = ES8_20000315_2_11.gif**
**giffile2 = ES8_20000315_2_12.gif**
**giffile3 = ES8_20000315_2_21.gif**
**giffile4 = ES8_20000315_2_22.gif**
**giffile5 = ES8_20000315_2_31.gif**
**giffile6 = ES8_20000315_2_32.gif**
**giffile7 = ES8_20000315_2_41.gif**
**giffile8 = ES8_20000315_2_42.gif**
**giffile9 = ES8_20000315_2_51.gif**
**giffile10 = ES8_20000315_2_52.gif**
**giffile11 = ES8_20000315_2_61.gif**
**giffile12 = ES8_20000315_2_62.gif**
**giffile13 = ES8_20000315_2_71.gif**
**giffile14 = ES8_20000315_2_72.gif**
**giffile15 = ES8_20000315_2_81.gif**
**giffile16 = ES8_20000315_2_82.gif**
**giffile17 = ES8_20000315_2_9.gif**

**# LOG FILES**

**logfile1 = CER2.2P1_LogStatus_Terra-FM1_Test_000000.20000315**
**logfile2 = CER2.2P1_LogReport_Terra-FM1_Test_000000.20000315**
**logfile3 = CER2.2P1_LogUser_Terra-FM1_Test_000000.20000315**

# Sample Input File Listing for PGE CER2.2P1- CONT'

**# USER RUN-TIME PARAMETERS**

**Satellite = Terra**
**Instrument = FM1**

**ksc = 2**
**adm = 1**
**isw_offset = 2**
**iscc_algr = 2**

# Sample Input File Listing for PGE CER2.3P1

```
#  METADATA RUN-TIME PARAMETERS

PGEName = CER2.3P1
SamplingStrategy = Terra-FM1
ProductionStrategy = Test
CERDataDateYear = 2000
CERDataDateMonth = 04
CERDataDateDay = 01
ConfigurationCode = 000000
SWsccr = 000
DATAsccr = 000


# I/O DIRECTORIES

tkrdir = /opt/net/TK5.2.7v1/TOOLKIT/runtime
tkddir = /opt/net/TK5.2.7v1/TOOLKIT/database
clddir = /CERES/lib/sgi64_lib/data
rcfdir = /CERES/erbelike/rcf/pcf
mcfdir = /CERES/erbelike/rcf/mcf
scrdir = /CERES/erbelike/data/scr/CER2.3_Terra-FM1_Test_000000.20000401
ancdir = /CERES/erbelike/data/ancillary/static
dyndir = /CERES/erbelike/data/ancillary/dynamic
logdir = /CERES/erbelike/data/runlogs
inpdir = /CERES/instrument/data/out_comp
invdir = /CERES/erbelike/data/out_comp/data/inv
ddbdir = /CERES/erbelike/data/out_comp/data/ddb


# ANCILLARY INPUT FILES

ancfile1 = NIISCOLD.19980904
ancfile2 = NIPSC.19991123
DAY = ceres_SI_FM1_day.20000105
NIGHT = ceres_SI_FM1_night.20000105
TOLERANCES = map_FM1_fullscan.20010612
ancfile3 = CER_SNOW_CERES_Test_000000.200003
ancfile4 = BIISW02.19980130
ancfile5 = BIILWSP.19980130
```

# Sample Input File Listing for PGE CER2.3P1 - CONT'

```
# I/O FILES

inpfile1 = CER_PRES8_Terra-FM1_Test_000000.20000401

outfile1 = CER_CMSGX_Terra-FM1_Test_000000.20000401
outfile2 = CER_CQCIX_Terra-FM1_Test_000000.20000401
outfile3 = CER_EID6X_Terra-FM1_Test_000000.20000401
outfile5 = CER_CXDR_Terra-FM1_Test_000000.20000401
outfile6 = CER_CQCD_Terra-FM1_Test_000000.20000401


#  LOG FILES

logfile1 = CER2.3P1_LogStatus_Terra-FM1_Test_000000.20000401
logfile2 = CER2.3P1_LogReport_Terra-FM1_Test_000000.20000401
logfile3 = CER2.3P1_LogUser_Terra-FM1_Test_000000.20000401


#   USER RUN-TIME PARAMETERS

Satellite = Terra
Instrument = FM1

ksc    = 2
adm   = 1
isw_offset = 2
iscc_algr  = 2
```

# Sample Input File Listing for PGE CER2.3P2

```
#  METADATA RUN-TIME PARAMETERS

PGEName = CER2.3P2
SamplingStrategy = Terra-FM1
ProductionStrategy = Test
CERDataDateYear = 2000
CERDataDateMonth = 02
CERDataDateDay = 29
ConfigurationCode = 000000
SWsccr = 000
DATAsccr = 000


# I/O DIRECTORIES

tkrdir = /opt/net/TK5.2.7v1/TOOLKIT/runtime
tkddir = /opt/net/TK5.2.7v1/TOOLKIT/database
clddir = /CERES/lib/sgi64_lib/data
rcfdir = /CERES/erbelike/rcf/pcf
mcfdir = /CERES/erbelike/rcf/mcf
scrdir = /CERES/erbelike/data/scr/CER2.3_Terra-FM1_Test_000000.20000229
ancdir = /CERES/erbelike/data/ancillary/static
dyndir = /CERES/erbelike/data/ancillary/dynamic
logdir = /CERES/erbelike/data/runlogs
inpdir = /CERES/instrument/data/out_comp
invdir = /CERES/erbelike/data/out_comp/data/inv
ddbdir = /CERES/erbelike/data/out_comp/data/ddb


# ANCILLARY INPUT FILES

ancfile1 = NIISCOLD.19980904
ancfile2 = NIPSC.19991123
DAY = ceres_SI_FM1_day.20000105
NIGHT = ceres_SI_FM1_night.20000105
TOLERANCES = map_FM1_fullscan.20010612
ancfile3 = CER_SNOW_CERES_Test_000000.200003
ancfile4 = BIISW02.19980130
ancfile5 = BIILWWN.19980130
```

# Sample Input File Listing for PGE CER2.3P2 - CONT'

```
# I/O FILES

inpfile1 = CER_PRES8_Terra-FM1_Test_000000.20000229

outfile1 = CER_CMSGX_Terra-FM1_Test_000000.20000229
outfile2 = CER_CQCIX_Terra-FM1_Test_000000.20000229
outfile3 = CER_EID6X_Terra-FM1_Test_000000.20000229
outfile5 = CER_CXDR_Terra-FM1_Test_000000.20000229
outfile6 = CER_CQCD_Terra-FM1_Test_000000.20000229


#  LOG FILES

logfile1 = CER2.3P2_LogStatus_Terra-FM1_Test_000000.20000229
logfile2 = CER2.3P2_LogReport_Terra-FM1_Test_000000.20000229
logfile3 = CER2.3P2_LogUser_Terra-FM1_Test_000000.20000229


#   USER RUN-TIME PARAMETERS

Satellite = Terra
Instrument = FM1

ksc    = 2
adm   = 1
isw_offset = 2
iscc_algr  = 2
```

# Sample Input File Listing for PGE CER2.4P1

```
#  METADATA RUN-TIME PARAMETERS

PGEName = CER2.4P1
SamplingStrategy = Terra-FM1
ProductionStrategy = Test
CERDataDateYear = 2001
CERDataDateMonth = 05
CERDataDateDay = 20
ConfigurationCode = 000000
SWsccr = 000
DATAsccr = 000


#  I/O DIRECTORIES

tkrdir = /opt/net/TK5.2.7v1/TOOLKIT/runtime
tkddir = /opt/net/TK5.2.7v1/TOOLKIT/database
clddir = /CERES/lib/sgi64_lib/data
inpdir = /CERES/erbelike/data/input
rcfdir = /CERES/erbelike/rcf/pcf
mcfdir = /CERES/erbelike/rcf/mcf
scrdir = /CERES/erbelike/data/scr/CER2.4_Terra-FM1_Test_000000.20010520
ancdir = /CERES/erbelike/data/ancillary/static/scc
dyndir = /CERES/erbelike/data/ancillary/dynamic
logdir = /CERES/erbelike/data/runlogs
wscdir = /CERES/erbelike-1/Ver4_432/erbelike/Web/scc_trend/data/

#  ANCILLARY INPUT FILES

#
# Spectral Response Functions
#
SWstartFile    = SRF_Terra-FM1_SW.20000224.20011204
TOTALstartFile = SRF_Terra-FM1_TOT.20000224.20011204
WNstartFile    = SRF_Terra-FM1_WN.20000224.20011204
SWendFile    = SRF_Terra-FM1_SW.20011204.20011204
TOTALendFile = SRF_Terra-FM1_TOT.20011204.20011204
WNendFile    = SRF_Terra-FM1_WN.20011204.20011204
```

## Sample Input File Listing for PGE CER2.4P1 - CONT'

```
#
# Modtran Files
#
anc_dayfile = ceres_SI_FM1_day.20020102
ancfile2001 = dc_sz00.spectra.tp7
ancfile2002 = dc_sz41.spectra.tp7
ancfile2003 = dc_sz60.spectra.tp7
ancfile2004 = dc_sz75.spectra.tp7
ancfile2005 = dc_sz85.spectra.tp7
ancfile2006 = sno_sz00L.tp7
ancfile2007 = sno_sz41L.tp7
ancfile2008 = sno_sz60L.tp7
ancfile2009 = sno_sz75L.tp7
ancfile2010 = sno_sz85L.tp7
ancfile2011 = oceclr_sz00L.tp7
ancfile2012 = oceclr_sz41L.tp7
ancfile2013 = oceclr_sz60L.tp7
ancfile2014 = oceclr_sz75L.tp7
ancfile2015 = oceclr_sz85L.tp7
ancfile2016 = ocecld_sz00L.tp7
ancfile2017 = ocecld_sz41L.tp7
ancfile2018 = ocecld_sz60L.tp7
ancfile2019 = ocecld_sz75L.tp7
ancfile2020 = ocecld_sz85L.tp7
ancfile2021 = lnd_sz00L.tp7
ancfile2022 = lnd_sz41L.tp7
ancfile2023 = lnd_sz60L.tp7
ancfile2024 = lnd_sz75L.tp7
ancfile2025 = lnd_sz85L.tp7
ancfile2026 = dc_vz.spectra.tp7
ancfile2027 = lnd_vz.tp7
ancfile2028 = sno_vz.tp7
ancfile2029 = oceclr_vz.tp7
ancfile2030 = ocecld_vz.tp7


#  I/O FILES


# Spectral Master Files

dayfile   = CER_SCCD_Terra-FM1_Test_000000.20010520
nightfile = CER_SCCN_Terra-FM1_Test_000000.20010520
```

## Sample Input File Listing for PGE CER2.4P1 - CONT'

```
#  WEB FILES

sccw_file1 = SCCtrend_Terra-FM1_SWtrend.web
sccw_file2 = SCCtrend_Terra-FM1_TOTtrend.web
sccw_file3 = SCCtrend_Terra-FM1_WNtrend.web
sccw_file4 = SCCtrend_Terra-FM1_TOT-SWtrend.web
scclogfile   = SCCtrend_Terra-FM1.log
plotfile      = SCCtrend_plot_Terra-FM1.gif

#  LOG FILES

logfile1 = CER2.4P1_LogStatus_Terra-FM1_Test_000000.20010520
logfile2 = CER2.4P1_LogReport_Terra-FM1_Test_000000.20010520
logfile3 = CER2.4P1_LogUser_Terra-FM1_Test_000000.20010520


#   USER RUN-TIME PARAMETERS

Satellite = Terra
Instrument = FM1

# Interpolation Dates

SWstartDate = 20000224
SWendDate   = 20011204
TOTALstartDate = 20000224
TOTALendDate   = 20011204
WNstartDate = 20000224
WNendDate   = 20011204

# Interpolation Intervals

SWInterpolationInterval    = 648
TOTALInterpolationInterval = 648
WNInterpolationInterval    = 648
SWCurrentInterval    = 450
TOTALCurrentInterval = 450
WNCurrentInterval    = 450

# Channel Codes :    1 =  SW, 2 = TOTAL, 3 = WN
#                    0 =  No Interpolation

channel_code = 123
```